

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

T 27 S R 3 W

S 4	S 3
S 9	S 10

1958

from which

A fir, 6 ins. diam., bears N. $60\frac{1}{2}^\circ$ E., 13 lks. dist.,
mkd. T27S R3W S3 BT.

A fir, 13 ins. diam., bears S. $51\frac{1}{2}^\circ$ E., 59 lks. dist.,
mkd. T27S R3W S10 BT.

A fir, 10 ins. diam., bears S. $26\frac{1}{2}^\circ$ W., 43 lks. dist.,
mkd. T27S R3W S9 BT.

A fir, 13 ins. diam., bears N. $67\frac{3}{4}^\circ$ W., 67 lks. dist.,
mkd. T27S R3W S4 BT.

Deposit County Surveyor's iron pipe alongside iron post.

N. $1^\circ 49'$ E., bet. secs. 3 and 4.

Ascend 344 ft. over SW. slope, through heavy timber and dense undergrowth.

20.275 Point for the S 1/16 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground with brass cap mkd.

S 1/16

S 4	S 3
-----	-----

1958

from which

A fir, 9 ins. diam., bears S. 20° E., 52 lks. dist.,
mkd. S 1/16 S3 BT.

A fir, 14 ins. diam., bears N. 4° W., 69 lks. dist.,
mkd. S 1/16 S4 BT.

Ascend 39 ft. over SW. slope.

23.54 Ridge, bears NW. and SE.; desc. 213 ft. over NE. slope.

40.55 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 S R 3 W

S 4	S 3
-----	-----

1958

from which

A white fir, 10 ins. diam., bears S. 16° E., 73 lks. dist.,
mkd. $\frac{1}{4}$ S3 BT.

A cedar, 9 ins. diam., bears N. $45\frac{1}{2}^\circ$ W., 54 lks. dist.,
mkd. $\frac{1}{4}$ S4 BT.