

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

A fir, 16 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ W., 65 lks. dist.,
mkd. T27S R3W S17 BT.

Deposit county surveyor's iron pipe alongside iron post.

N. $1^{\circ} 00'$ E., bet. secs. 16 and 17.

Ascend 56 ft. over SW. slope, through heavy timber and dense undergrowth.

- 1.90 Top of ascent, slopes SW.; desc. 65 ft. over NW. slope.
- 5.75 Foot of descent, slopes SW.; asc. 120 ft. over SW. slope.
- 12.05 Spur, slopes SW.; desc. 42 ft. over broken NW. slope.
- 18.05 Foot of descent, slopes SW.; asc. 65 ft. over SW. slope.
- 21.35 Spur ridge, bears SE. and NW. curving to NE.; desc. 2 ft. over NE. slope.
- 23.80 Same spur ridge, bears NE. and SW. curving to SE.; desc. 239 ft. over NW. slope.
- 41.06 The $\frac{1}{4}$ sec. cor. of secs. 16 and 17, determined at record bearing and distance from the two original bearing trees:
- A cedar, 30 ins. diam., bears S. 50° E., 31 lks. dist.,
bark scribed $\frac{1}{4}$ S BT.
- A fir, 30 ins. diam., bears N. 75° W., 29 lks. dist.,
bark scribed $\frac{1}{4}$ S BT and also axe marks and a healed blaze.
- At the corner point
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
- T 27 S R 3 W

$\frac{1}{4}$

S 17 | S 16

1958
- from which
- A madrone, 10 ins. diam., bears S. $20\frac{1}{4}^{\circ}$ E., 42 lks. dist.,
mkd. $\frac{1}{4}$ S16 BT.
- A madrone, 8 ins. diam., bears N. $32\frac{1}{4}^{\circ}$ W., 60 lks. dist.,
mkd. $\frac{1}{4}$ S17 BT.
-
- N. $0^{\circ} 14'$ W., beginning new measurement.
- Descend 273 ft. over NW. slope.
- 12.30 Jim Creek, 12 lks. wide, course NE.; asc. 122 ft. over SE. slope.
- 13.65 Dirt access road, 30 lks. wide, bears NE. and SW.
- 20.05 Spur, slopes E.; desc. 23 ft. over NE. slope.
- 24.60 Creek, 2 lks. wide, course SE.; asc. 191 ft. over SW. slope.
- 33.15 Spur, slopes S.; asc. 68 ft. over SE. slope.