

County Surveyor's Record, Douglas County, Oregon

31

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS
79.09

The cor. of secs. 8, 9, 16, and 17.

Land, rolling hills.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, and chinquapin; undergrowth, poison oak, salal, vinemaple, madrone, and fir, and hemlock reproduction.

From the cor. of secs. 7, 8, 17, and 18, perpetuated and recorded by J. W. Byron, Deputy County Surveyor, in 1957, at record bearing and distance from two original bearing trees and record bearing from a third original bearing tree, monumented with an iron pipe, 1 in. diam., firmly set in a mound of stone, 3 ft. base, to top, with brass cap mkd.

County Surveyors

T 27 S

S 7 | S 8

S 18 | S 17

R 3 W

Office 1957

from which original bearing trees:

A fir, 25 ins. diam., bears S. 28° E., 8 lks. dist., bark scribed S17 BT.

A fir, 17 ins. diam., bears S. 17° W., 15 lks. dist., bark scribed S18 T27S R3W BT.

A cedar, 28 ins. diam., bears N. 63° W., 12 lks. dist., bark scribed S7 T27S R3W BT. (Record distance 8 lks.)

and county surveyor's bearing tree:

A madrone, 36 ins. diam., bears N. 80° E., 97 lks. dist., bark scribed S8 T27 R3W.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., on an X marked on bedrock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.

T 27 S R 3 W

S 7 | S 8

S 18 | S 17

1958

from which

A chinquapin, 6 ins. diam., bears N. 29° E., 32 lks. dist., mkd. T27S R3W S8 BT.

A fir, 23 ins. diam., bears S. 71½° E., 62 lks. dist., mkd. T27S R3W S17 BT.

A fir, 16 ins. diam., bears S. 59° W., 38 lks. dist., mkd. T27S R3W S18 BT.

A fir, 35 ins. diam., bears N. 76¾° W., 30 lks. dist., mkd. T27S R3W S7 BT.

Deposit county surveyor's iron pipe alongside iron post.

N. 88° 59' W., bet. secs. 7 and 18.

Descend 81 ft. over SW. slope, through heavy timber and dense undergrowth.