

County Surveyor's Record, Douglas County, Oregon

33

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

37.75

Spur, slopes E.; desc. 27 ft. over NE. slope.

40.19

The $\frac{1}{4}$ sec. cor. of secs. 7 and 8, perpetuated with a wooden stake, 2 x 2 ins. cross section, firmly set, 10 ins. above ground, with $\frac{1}{4}$ S scribed on the E. face, at record bearing and distance from the two original bearing trees:

A fir, 35 ins. diam., bears S. 80° E., 21 lks. dist., bark scribed $\frac{1}{4}$ S.

A cedar, 33 ins. diam., bears N. 25° W., 38 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 27 S R 3 W

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 7 \text{ | S } 8 \\ | \\ 1958 \end{array}$$

FD. 1975
Ben. Admin. Survey
CLB R. 11. 1975

from which

A madrone, 22 ins. diam., bears S. $84\frac{1}{2}^{\circ}$ E., 54 lks. dist., mkd. $\frac{1}{4}$ S8 BT.

A cedar, 13 ins. diam., bears N. 65° W., 57 lks. dist., mkd. $\frac{1}{4}$ S7 BT.

N. $3^{\circ} 12'$ E., beginning new measurement.

Descend 305 ft. over NE. slope changing to N. slope, through heavy timber and dense undergrowth.

9.10

Leave timber, enter logged and burned area, edge bears E. and W.

14.05

Foot of descent, slopes E.; asc. 38 ft. over SE. slope.

20.495

Point for the N $1/16$ sec. cor. of secs. 7 and 8.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{N } 1/16 \\ | \\ \text{S } 7 \text{ | S } 8 \\ | \\ 1958 \end{array}$$

from which

A fir, 8 ins. diam., bears S. $79\frac{1}{2}^{\circ}$ E., 27 lks. dist., mkd. N $1/16$ S8 BT.

A fir, 10 ins. diam., bears N. 53° W., 39 lks. dist., mkd. N $1/16$ S7 BT.

Ascend 256 ft. over SE. slope.

40.99

Point for the cor. of secs. 5, 6, 7, and 8, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground with brass cap mkd.