

## County Surveyor's Record, Douglas County, Oregon

35

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 27 ins. in the ground, with brass cap mkd.

T 26 S R 3 W
S 31   S 32
S 6   S 5
T 27 S
1958

from which

A fir, 26 ins. diam., bears N.  $61\frac{3}{4}^{\circ}$  E., 1202 lks. dist., mkd. T26S R3W S32 BT.A fir, 11 ins. diam., bears S.  $11\frac{3}{4}^{\circ}$  E., 128 lks. dist., mkd. T27S R3W S5 BT.A fir, 6 ins. diam., bears S.  $28^{\circ}$  W., 230 lks. dist., mkd. T27S R3W S6 BT.A fir, 6 ins. diam., bears N.  $52\frac{3}{4}^{\circ}$  W., 170 lks. dist., mkd. T26S R3W S31 BT.

Deposit local corner material alongside iron post.

Land, rolling hills.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, and oak; undergrowth, vine-maple, salal, hazel, poison oak, and ocean spray.

S.  $89^{\circ} 38'$  W., bet. secs. 6 and 7.

Ascend 106 ft. over SE. slope, through open pasture land.

13.52 Ridge, bears N. and S.; desc. 124 ft. over SW. slope.

19.855 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 6 and 7.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

E $\frac{1}{16}$ S 6
S 7
1958

from which

A fir, 9 ins. diam., bears N.  $26^{\circ}$  E., 49 lks. dist., mkd. E  $\frac{1}{16}$  S6 BT.A madrone, 9 ins. diam., bears S.  $49^{\circ}$  W., 68 lks. dist., mkd. E  $\frac{1}{16}$  S7 BT.

Leave pasture land, enter fir reproduction, edge bears NW. and SE.

Descend 286 ft. over SW. slope.

33.25 Skid road, 20 lks. wide, bears NE. and SW.

37.50 Creek, 2 lks. wide, course NW.; desc. 15 ft. over SW. slope.

38.50 Creek, 4 lks. wide, course N., also enter heavy timber, edge bears N. and S.; asc. 42 ft. over NE. slope.

39.71 Point for the  $\frac{1}{4}$  sec. cor. of secs. 6 and 7, at proportionate distance; there is no remaining evidence of the original corner.