

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 27 S., R. 3 W.

CHAINS Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 27 S R 3 W

¼ $\frac{S 6}{S 7}$

1958

*FLINT 1975
BEN ADRIAN SURVEY
SEE SEE FILE*

from which

A fir, 6 ins. diam., bears N. 36° E., 44 lks. dist., mkd. ¼ S6 BT.

A fir, 7 ins. diam., bears S. 71° W., 8 lks. dist., mkd. ¼ S7 BT.

Ascend 213 ft. over NE. slope.

53.15 Spur, slopes N.; desc. 69 ft. over NW. slope.

56.75 Ravine, drains N.; asc. 68 ft. over NE. slope.

59.565 Point for the W 1/16 sec. cor. of secs. 6 and 7.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W 1/16 $\frac{S 6}{S 7}$

1958

from which

A fir, 8 ins. diam., bears N. 25° E., 26 lks. dist., mkd. W 1/16 S6 BT.

A madrone, 23 ins. diam., bears S. 63° W., 27 lks. dist., mkd. W 1/16 S7 BT.

Ascend 89 ft. over NE. slope.

65.45 Ridge, bears N. and S.; desc. 337 ft. over NW. slope.

72.85 Skid road, 15 lks. wide, bears NE. and SW.

79.76 Skid road, 15 lks. wide, bears N. and S.

80.16 The cor. of secs. 1, 6, 7, and 12, on the W. bdy. of the Tp.

Land, rolling hills.

Soil, rocky clay.

Timber, fir, cedar, hemlock, and madrone; undergrowth, fir reproduction, vinemaple, salal, and hazel.

Remonumentation of Original Corners, T. 27 S., R. 3 W.

(Restoring the 1855 Survey by A. R. Flint and the 1882 Survey by S. C. Flint)

The following are remonumentations of original corner points in T. 27 S., R. 3 W., authorized under special instructions dated May 3, 1957, for the investigation and remonumentation of corner points included under Group 350, Oregon