

T. 27 S., R. 3 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, on the N. bdy. of T. 27 S., R. 3 W., determined at record bearing and distance from the two original bearing trees:

A red fir, 42 ins. diam., bears N. 60° W., 2 lks. dist., bark scribed $\frac{1}{4}$ S BT.

A cedar, 12 ins. diam., bears S., 2 lks. dist., with an old rotted blaze, no scribe marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, and in a mound of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

T 26 S R 3 W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{36}{1}$
 T 27 S
 1958

from which

A hemlock, 11 ins. diam., bears N. 4° E., 57 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

A yew, 8 ins. diam., bears S. 2° W., 53 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

The cor. of Tps. 26 and 27 S., Rs. 2 and 3 W., determined at record bearing and distance from the only remaining original bearing tree:

A fir, 32 ins. diam., bears S. 38° W., 7 lks. dist., with illegible scribe marks visible on a partially opened blaze.

and locally established bearing trees:

A rotted madrone, bears S. 22° W., 37 lks. dist., with illegible scribe marks visible on a partially opened blaze.

A madrone, 10 ins. diam., bears N. 39° W., 68 lks. dist., with illegible scribe marks visible on a partially opened blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 26 S
 R 3 W | R 2 W
 $\frac{S}{S}$ $\frac{36}{1}$ | $\frac{S}{S}$ $\frac{31}{6}$
 T 27 S
 1958

*FD. OK - 11/3/76
 G. LANGLITZ - SURVEYOR'S
 OFFICE - C.S. 59/26*

from which

A fir, 6 ins. diam., bears N. 51 $\frac{1}{2}$ ° E., 27 lks. dist., mkd. T26S R2W S31 BT.

A fir, 23 ins. diam., bears S. 46° E., 11 lks. dist., mkd. T27S R2W S6 BT.

A fir, 18 ins. diam., bears S. 76° W., 25 lks. dist., mkd. T27S R3W S1 BT.

A fir, 10 ins. diam., bears N. 24° W., 65 lks. dist., mkd. T26S R3W S36 BT.