

T. 27 S., R. 3 W.

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, on the E. bdy. of T. 27 S., R. 3 W., determined at record bearing and distance from the two original bearing trees:

A fir, 55 ins. diam., bears N. 35° E., 42 lks. dist., bark scribed $\frac{1}{4}$ S.

A rotted madrone stump, bears N. 15° W., 36 lks. dist., no marks remaining.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.

T 27 S
R 3 W $\frac{1}{4}$ R 2 W
|
S 1 | S 6
|
1958

from which

A fir, 18 ins. diam., bears S. 62° E., 36 lks. dist., mkd. $\frac{1}{4}$ S6 BT.

A cedar, 6 ins. diam., bears S. 51° W., 45 lks. dist., mkd. $\frac{1}{4}$ S1 BT.

The standard corner of secs. 34 and 35 only, on the sixth standard parallel south, the S. bdy. of T. 27 S., R. 3 W., perpetuated with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, 8 ins. above ground, at record bearing and distance from two original bearing trees:

A cedar, 32 ins. diam., bears N. 60° E., 50 lks. dist., with scribe marks T27S R3W S35 visible on a partially opened blaze.

An uprooted fir stump, bears N. 32° W., 125 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 27 ins. in the ground, with brass cap mkd.

SC
T 27 S R 3 W
S 34 | S 35
S 2
T 28 S
1958

from which

A cedar, 11 ins. diam., bears N. 2° E., 299 lks. dist., mkd. T27S R3W S35 SC BT.

A cedar, 12 ins. diam., bears N. $68\frac{1}{2}^\circ$ W., 155 lks. dist., mkd. T27S R3W S34 SC BT.

Deposit local corner material alongside iron post.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, perpetuated with a cedar post, 3 x 3 ins. cross section, firmly set, $2\frac{1}{2}$ ft. above ground, with scribe marks S8 on the NE. and S17 on the SW. faces, at record bearing and distance from the only remaining original bearing tree: