

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS	
8.20	Branch, 6 lks. wide, course N. 5° W.; asc. 87 ft. over NW. slope.
10.85	Top of ascent on bluffy N. slope; desc. 105 ft. along N. slope.
18.10	Left bank of Smith River, course N. 85° W.; thence in river.
20.73	The witness cor. to the closing cor. of Tps. 21 S., Rs. 9 and 10 W., bears S. 0° 27' E., 1.33 chs. dist., monumented with an iron post, 3 ins. diam., 10 ins. above ground, firmly set, marked and witnessed as described in the official record.
23.50	Right bank of Smith River; asc. 21 ft. over brushy bottom land, near river.
36.00	Fence, bears N. and S.; thence across open meadow.
38.60	Bernhardt's summer cottage, bears N. 74° E.
39.93	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked
	$\frac{1}{4} \frac{S \ 31}{S \ 6}$ 1953
	from which
	An iron post, 3 ft. long, 1 in. diam., set 32 ins. in the ground, for a reference monument, in fence row at S. side of Smith River Road, bears North, 308 lks. dist., marked $\frac{1}{4}$ S31 RM 1953 and an arrow pointing to the corner.
	An unmarked iron pipe, $1\frac{1}{2}$ ins. diam., projecting 10 ins. from a drill hole in solid rock, bears N. 82° 58' E., 5.33 chs. dist.
	An alder, 12 ins. diam., bears N. 86 $\frac{1}{4}$ ° E., 174 lks. dist., marked $\frac{1}{4}$ S31 BT.
	A cedar, 25 ins. diam., bears S. 86 $\frac{1}{4}$ ° W., 139 lks. dist., marked $\frac{1}{4}$ S6 BT.
	The $\frac{1}{4}$ sec. cor. is located 28 lks. N. of the right bank of Smith River.
	Descend 11 ft. along bottom land, in meadow.
43.20	Right bank of Smith River, 2 ins. to 6 ft. deep over bare rock bed, course S. 85° W.; asc. 3 ft. in river.
43.84	Bernhardt's summer cottage, bears N. 28° E.
51.84	Olsen Bros. sawmill, bears N. 52° 26' E.
55.00	Left bank of Smith River; asc. 4 ft. along bottom near river, through scattering alder.
57.00	Bluff, bears N. 80° E. and S. 80° W.; asc. 64 ft. over bluff.
58.00	Top of bluff, bears N. 80° E. and S. 80° W.; asc. 30 ft. over rolling bench, through heavy timber and dense undergrowth.
59.90	Power line, bears N. and S.
73.68	Cor. of fences extending N. and N. 89° 23' E.; thence along fence row.
75.00	Edge of bench, bears NW. and SE.; desc. 31 ft. over gradual NE. slope.

FD. 2/92
 BOB. W. W.
 M114-48
 FV
 2/13/92