

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS  
38.35

Barbed wire fence, bears N. 60° E. and S. 60° W.

39.72

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 32, determined from the original bearing trees, as follows:

A fir, 60 ins. diam., bears N. 64° E., 55 lks. dist., I uncover partial scribe marks of proper age at edge of old burned blaze. (Gesner reported this tree as a stump.)

A double maple, 40 ins. diam., bears S. 62 $\frac{1}{4}$ ° E., 183 lks. dist., bearing a healed blaze, which I open, but face of blaze at proper age is decayed. (Thiel record, 88 lks. dist.; Gesner, 90 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

Find OK By EIMSTAD  
Aug. 1781 M 89-13

$\frac{1}{4}$   $\frac{S\ 32}{S\ 5}$   
1953

from which new bearing trees,

A fir, 24 ins. diam., bears N. 3 $\frac{1}{2}$ ° E., 51 lks. dist., marked  $\frac{1}{4}$  S32 BT.

A fir, 24 ins. diam., bears S. 84° W., 20 lks. dist., marked  $\frac{1}{4}$  S5 BT.

From this point a fir, 16 ins. diam., bears N. 39° E., 26 lks. dist. with partially healed blazes on N., S., E., and W. sides.

The  $\frac{1}{4}$  sec. cor. is located at edge of bottom, bears N. and SE.

N. 88° 58' E., beginning new measurement.

Ascend 30 ft. over SW. slope, changing to S. slope.

7.90

Top of ascent on S. slope; desc. 25 ft. along broken S. slope.

11.00

Edge of bottom, bears N. 70° E. and S. 70° W.; asc. 5 ft. over bottom.

13.00

Buck Creek, 10 lks. wide, course S. 15° W.; asc. 2 ft. over bottom.

14.40

Buck Creek, 10 lks. wide, course N. 85° W.; asc. 12 ft. over broken SW. slope.

15.55

Dry bed of stream, 3 lks. wide, course S. 15° W.; asc. 100 ft. over SW. slope, changing to S. slope.

21.70

Top of ascent on S. slope; desc. 40 ft. over SE. slope.

24.15

Dry bed of stream, 6 lks. wide, course S. 30° W.; asc. 380 ft. over W. slope, changing to NW. slope.

33.30

Spur ridge, bears NE. and SW.; desc. 120 ft. over SE. slope.

39.15

Head of ravine, course S. 25° W.; asc. 5 ft. over SW. slope.

39.39

The cor. of secs. 4, 5, 32, and 33, monumented with a sandstone, 30 x 20 x 18 ins., with no marks remaining, from which the original bearing trees,

A fir stump, 36 ins. diam., bears N. 29 $\frac{1}{4}$ ° E., 33 lks. dist., with partial scribe marks visible. (Gesner record, bears N. 29° E.)