

## County Surveyor's Record, Douglas County, Oregon

6

## Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS  
48.90

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, determined at record bearing and distance from each of the original bearing trees, as follows:

A fir, 42 ins. diam., bears N.  $46^\circ$  E., 47 lks. dist., plainly blazed and healed. (Gesner record, 49 lks. dist.)

The shell of a fir stump, 10 ins. diam., bears S.  $36\frac{1}{4}^\circ$  W., 20 lks. dist., with no marks remaining. (Gesner record, bears S.  $36^\circ 45'$  W.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$$\frac{1}{4} \begin{array}{l} S 33 \\ S 4 \\ 1953 \end{array}$$

from which new bearing trees,

A fir, 15 ins. diam., bears N.  $18^\circ$  E., 8 lks. dist., marked  $\frac{1}{4}$  S33 BT.

A fir, 10 ins. diam., bears S.  $54^\circ$  E., 5 lks. dist., marked  $\frac{1}{4}$  S4 BT.

N.  $88^\circ 45'$  E., beginning new measurement.

Descend 560 ft. over broken SE. slope.

16.90 Dry bed of a stream, 3 lks. wide, course N.  $60^\circ$  E.; asc. 10 ft. over NW. slope.

17.30 Low point of spur, slopes N.  $40^\circ$  E.; desc. 15 ft. over E. slope.

17.90 Dry bed of a stream, 4 lks. wide, course N.  $15^\circ$  E.; 1 ch. S. of junction with that noted at 16.90 chs.; asc. 10 ft. over NW. slope.

18.30 Top of ascent at edge of bench, bears N.  $15^\circ$  E. and S.  $15^\circ$  W.; desc. 38 ft. over gentle NE. slope of bench.

23.80 Top of a bluff, bears N. and S.; desc. 96 ft. over E. slope of bluff.

25.65 Vincent Creek, 60 lks. wide, course N.; asc. 147 ft. over general W. slope.

27.78 Graded clay road, bears N. and S.

40.04 The cor. of secs. 33 and 34 only, determined at record distance from each of the original bearing trees, as follows:

A hemlock snag, 40 ins. diam., bears N.  $38^\circ$  E., 67 lks. dist., with scribe marks T20 and BT visible on partly decayed face of blaze. (Thiel record, bears N.  $46^\circ$  E.; Gesner record, bears N.  $37^\circ$  E., 68 lks. dist.)

A hemlock, 40 ins. diam., bears S.  $21^\circ$  E., 36 lks. dist., with scribe marks T21, R9, and S3 visible on opened and decaying blaze.

An alder stump, 20 ins. diam., bears S.  $63\frac{1}{2}^\circ$  W., 67 lks. dist., with only axe marks remaining.

A fir, 58 ins. diam., bears N.  $14^\circ$  W., 46 lks. dist., plainly blazed and healed.

At the corner point