

County Surveyor's Record, Douglas County, Oregon

7

Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 9 W
 S 33 | S 34
 T 21 S R 9 W
 S 4
 1953

F.D. BENT - STRAIGHTENED
 2/11/54 - L. BARBERS
 A 90-53 -
 DUGAN MAC-MANUS
 JUN 28 1954

from which a new bearing tree,

A cedar, 54 ins. diam., bears N. $88\frac{1}{2}^{\circ}$ E., 48 lks. dist., marked T20S R9W S34 BT. (This cedar is the line tree mentioned by Thiel as being 46 lks. dist., and by Gesner as being 48 lks. dist., and has healed blazes on E. and W. sides slightly S. of center. No other suitable bearing tree is available in the NE. quadrant.)

Land, mountainous. Soil, sandy and rocky clay loam. Timber, fir, hemlock, cedar, alder, and maple. Undergrowth, vine maple, evergreen huckleberry, salmonberry, hazel, arrowwood, rhododendron, salal, and poison oak.

N. $89^{\circ} 22'$ E., along the S. bdy. of sec. 34.

Ascend 380 ft. over W. slope, through heavy timber and dense undergrowth.

11.50 Spur, slopes S. 60° W.; asc. 160 ft. over broken SW. slope.

13.45 The closing cor. of secs. 3 and 4, T. 21 S., R. 9 W., bears North, 0.36 chs. dist., monumented with a fir post, $4\frac{1}{2}$ ft. long, 4 ins. square, firmly set 18 ins. in the ground, from which the original bearing trees,

A fir, 40 ins. diam., bears S. $67\frac{1}{2}^{\circ}$ E., 68 lks. dist., plainly blazed and healed.

A sawed fir stump, 40 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ W., 47 lks. dist., plainly blazed and healed.

A fir, 30 ins. diam., bears N. 57° W., 58 lks. dist., plainly blazed and healed.

19.40 Spur ridge, bears N. 50° W. and S. 50° E.; desc. 130 ft. over broken NE. slope.

27.15 Spring branch, 3 lks. wide, course N.; asc. slightly along N. slope.

28.15 Ravine, course N. 60° W.; asc. 300 ft. over SW. slope, changing to W. slope.

37.00 Top of slope, bears N. and SE.; asc. 5 ft. over flat.

40.02 The $\frac{1}{4}$ sec. cor. of sec. 34 only, marked by the decayed shell of a fir stump, 48 ins. diam., with partial scribe marks visible on the bark, from which the original bearing trees,

A cedar, 50 ins. diam., bears N. 51° E., 70 lks. dist., plainly blazed and healed. (Record, bears N. 46° E.)

The stump hole of an uprooted fir, 32 ins. diam., bears S. 88° W., 72 lks. dist., marked $\frac{1}{4}$ S on bark blaze on fallen trunk.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked