

County Surveyor's Record, Douglas County, Oregon

9

Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS 2.35	Scare Creek, 10 lks. wide, course N. 20° W.; asc. 350 ft. over general W. slope.
10.65	The closing cor. of secs. 2 and 3, T. 21 S., R. 9 W., bears North, 0.15 chs. dist., monumented with a sandstone, 10 x 8 x 7 ins., firmly set 6 ins. in the ground, marked with 2 notches on E. edge, alongside which has been driven a cedar post, 4 ins. square, 3 ft. above ground; from the sandstone, the original bearing trees, <ul style="list-style-type: none"> A fir, 48 ins. diam., bears N. 4$\frac{1}{4}$° E., 30 lks. dist., plainly blazed and healed. (Record bearing, N. 4$\frac{1}{4}$° W.) A fir, 56 ins. diam., bears S. 9° E., 75 lks. dist., plainly blazed and healed. A fir, 60 ins. diam., bears S. 28° W., 100 lks. dist., plainly blazed and healed. Ascend 210 ft. over general W. slope.
15.30	Spur ridge, bears N. 65° W. and S. 65° E.; desc. 30 ft. along N. slope.
22.65	Ravine, course N. 70° W.; asc. 160 ft. over W. slope.
27.05	Spur, slopes NW.; asc. 65 ft. along broken N. slope.
40.07	Point for the $\frac{1}{4}$ sec. cor. of sec. 35 only, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \text{ S } 35$ 1954 from which <ul style="list-style-type: none"> A maple, 20 ins. diam., bears N. 20$\frac{1}{2}$° E., 29 lks. dist., marked $\frac{1}{4}$ S35 BT. A hemlock, 8 ins. diam., bears N. 61° W., 36 lks. dist., marked $\frac{1}{4}$ S35 BT. Ascend 5 ft. along N. slope.
41.05	Spur ridge, bears NE. and S. 70° W.; desc. 90 ft. over SE. slope.
44.50	Foot of descent on S. slope; asc. 20 ft. over SW. slope.
46.50	Spur ridge, bears N. 20° W. and S. 20° E.; desc. 270 ft. over NE. slope.
53.60	Branch, 2 lks. wide, course S. 10° E.; asc. 30 ft. along broken S. slope.
56.60	Ravine, course S. 5° W.; desc. 1 ft. along broken S. slope.
62.70	Branch, 2 lks. wide, flowing on bare rock bed, course S. 20° W.; asc. 120 ft. over broken SW. slope.
70.25	Shallow ravine, course S. 20° W.; asc. 280 ft. over general W. slope.
80.14	The cor. of secs. 35 and 36 only, marked by the shell of a fir stump, 18 ins. diam., nearly rotted away, from which the remaining original bearing trees, <ul style="list-style-type: none"> A fir snag, 38 ins. diam., bears N. 81$\frac{1}{2}$° E., 232 lks. dist., plainly blazed and healed. (Thiel record, bears N. 80$\frac{1}{2}$° E., 170 lks. dist.; Gesner record, bears N. 81° E., 232 lks. dist.)