

## County Surveyor's Record, Douglas County, Oregon

10

## Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS

A fir, 50 ins. diam., bears S.  $81\frac{1}{2}^{\circ}$  E., 177 lks. dist., marked T21S R9W BT on the bark. (Thiel record, bears S.  $81\frac{1}{2}^{\circ}$  E., 210 lks. dist.; Gesner record, bears S.  $81\frac{1}{2}^{\circ}$  E., 177 lks. dist.)

An alder, 23 ins. diam., bears N.  $12^{\circ}$  W., 8 lks. dist., very cleanly healed. (Thiel record, bears N.  $5^{\circ}$  W., 5 lks. dist.; Gesner record, bears N.  $12^{\circ}$  W., 8 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{r} T\ 20\ S\ R\ 9\ W \\ \underline{S\ 35\ |S\ 36} \\ T\ 21\ S\ R\ 9\ W \\ S\ 2 \\ 1954 \end{array}$$

from which new bearing trees,

A hemlock, 14 ins. diam., bears N.  $53\frac{1}{2}^{\circ}$  E., 23 lks. dist., marked T20S R9W S36 BT.

A hemlock, 12 ins. diam., bears N.  $18^{\circ}$  W., 14 lks. dist., marked T20S R9W S35 BT.

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, and alder. Undergrowth, vine maple, salmonberry, hazel, rhododendron, evergreen huckleberry, arrowwood, and salal.

N.  $89^{\circ} 00'$  E., along the S. bdy. of sec. 36.

Ascend 18 ft. over gradual SW. slope, through heavy timber and dense undergrowth.

2.70 Spur ridge, bears N.  $10^{\circ}$  W. and S.  $10^{\circ}$  E.; desc. 295 ft. over E. slope.

9.80 Branch, 2 lks. wide, course S.; asc. 90 ft. over SW. slope.

12.44 The closing cor. of secs. 1 and 2, T. 21 S., R. 9 W., determined at record distance from each of the original bearing trees, as follows:

A fir, 60 ins. diam., bears N.  $6^{\circ}$  E., 69 lks. dist., plainly blazed and healed. (Record bearing, N.  $6^{\circ}$  W.)

A fir, 42 ins. diam., bears S.  $77\frac{1}{4}^{\circ}$  E., 56 lks. dist., plainly blazed and healed. (Record bearing, S.  $73^{\circ}$  E.)

A fir, 70 ins. diam., bears S.  $9^{\circ} 45'$  W., 154 lks. dist., plainly blazed and healed. (Record bearing, S.  $11\frac{1}{2}^{\circ}$  W.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

$$\begin{array}{r} T\ 20\ S\ R\ 9\ W \\ \underline{S\ 36} \\ S\ 2\ |S\ 1 \\ T\ 21\ S\ R\ 9\ W \\ C\ C \\ 1954 \end{array}$$

Ascend 3 ft. over SW. slope.

12.65 Spur, slopes S.  $15^{\circ}$  E.; desc. 20 ft. over SE. slope.