

County Surveyor's Record, Douglas County, Oregon

11

Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS	
14.05	Ravine, course S.; asc. 230 ft. over SW. slope.
33.00	Spur ridge, bears N. 25° E. and S.; desc. 185 ft. over SE. slope.
38.10	Head of ravine, course S. 10° E.; asc. 25 ft. over SW. slope.
40.40	Point of steep, rocky spur, slopes S.; desc. 6 ft. along steep S. slope.
40.63	The $\frac{1}{4}$ sec. cor. of sec. 36 only, monumented with a shattered sandstone, 16 x 12 x 8 ins., with no marks remaining, loosely set in a small mound of stone, from which the original bearing trees, <p style="margin-left: 40px;">An uprooted fir, 48 ins. diam., plainly blazed and healed, the stump hole of which bears N. 52$\frac{1}{2}$° W., 46 lks. dist.</p> <p style="margin-left: 40px;">A fir, 48 ins. diam., bears S. 89° E., 29 lks. dist., marked $\frac{1}{4}$ S BT on bark blaze. (Gesner record, bears S. 87° E.)</p> <p>At the corner point</p> <p>Set an iron post, 16 ins. long, 1 in. diam., 8 ins. in a drill hole in solid rock, with brass cap marked</p> <p style="text-align: center;">$\frac{1}{4}$ S 36</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">1954</p> <p>from which new bearing trees,</p> <p style="margin-left: 40px;">A fir, 31 ins. diam., bears N. 9° 45' E., 72 lks. dist., marked $\frac{1}{4}$ S36 BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 70$\frac{1}{2}$° W., 26 lks. dist., marked $\frac{1}{4}$ S36 BT.</p> <p>Reset the sandstone alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 83° 01' E., beginning new measurement.</p> <p>Descend 33 ft. over SE. slope.</p>
0.98	Branch, 1 lk. wide, course S.; asc. 370 ft. over broken SW. slope.
27.50	Ridge, the divide bet. Scare Creek and Beaver Creek, bears N. 60° W. and S. 80° E.; asc. 23 ft. along broken N. slope.
32.35	Spur, slopes N. 10° E.; desc. 230 ft. over E. slope.
37.00	Head of ravine, course N.; asc. 20 ft. along N. slope.
39.25	Spur, slopes NE.; desc. 370 ft. over SE. slope.
48.40	Ravine, course N. 83° E.; from S. 70° W.; desc. 10 ft. along ravine.
49.60	Branch, 2 lks. wide, course N. 40° E., at mouth of ravine; asc. 62 ft. over NW. slope.
51.42	Intersect the W. bdy. of sec. 31, T. 20 S., R. 8 W., at proportionate point (latitudinally) for the closing cor. of Tps. 20 and 21 S., R. 9 W., there is no remaining evidence of the original corner. <p>Set an iron post, 3 ft. long, 3 ins. diam., 28 ins. in the ground, with brass cap marked</p>