

County Surveyor's Record, Douglas County, Oregon

12

Dependent Resurvey of the South Boundary of T. 20 S., R. 9 W.

CHAINS

	T 20 S	
	R 9 W	T 20 S
CC	S 36	S 31
	S 1	
	T 21 S	R 8 W
	1954	

from which

A cedar, 10 ins. diam., bears N. 65° W., 67 lks. dist.,
marked T20S R9W S36 CC BT.

A fir, 18 ins. diam., bears S. 31 $\frac{1}{4}$ ° W., 55 lks. dist.,
marked T21S R9W S1 CC BT.

From this point the $\frac{1}{4}$ sec. cor. of sec. 31, T. 20 S., R. 8 W., bears
N. 1° 27' E., 1.03 chs. dist., monumented with an iron post, 1 in.
diam., 8 ins. above ground, firmly set, marked and witnessed as
described in the official record.

Land, mountainous. Soil, sandy and rocky clay loam. Timber, fir,
cedar, hemlock, maple, and alder. Undergrowth, vine maple, ever-
green huckleberry, salmonberry, hazel, arrowwood, rhododendron, and
salal.

Dependent Resurvey of a Portion of the W. Bdy. of T. 19 S., R. 8 W.
(Restoring the 1891 survey by Charles M. Collier)

Beginning at the cor. of Tps. 19 and 20 S., R. 8 W., on the E. bdy.
of sec. 1, T. 20 S., R. 9 W., which is monumented with an iron post,
3 ins. diam., 8 ins. above ground, firmly set, marked and witnessed
as described in the official record.

N. 0° 04' W., along the W. bdy. of sec. 31, marking and blazing
the true line.

Descend 215 ft. over N. slope, through heavy timber and dense under-
growth.

3.90 Enter bottom land; edge bears N. 80° E. and S. 80° W.; desc. 5 ft.
over bottom.

4.80 West Fork of Smith River, 25 lks. wide, course S. 70° W.; asc. 24
ft. over bottom.

7.39 An uprooted fir, 48 ins. diam., marked with two hacks on N. and S.
sides.

9.00 Leave bottom land; edge bears N. 70° E. and S. 70° W.; asc. 200 ft.
over S. slope.

21.75 Spur, slopes SE.; desc. 50 ft. over NE. slope.

25.65 Branch, 4 lks. wide, course S. 50° E.; asc. 210 ft. over SW. slope,
changing to S. slope.

37.93 The closing cor. of Tps. 19 and 20 S., R. 9 W.

Ascend 60 ft. over S. slope.

39.95 The $\frac{1}{4}$ sec. cor. of sec. 31 only, marked by the stump hole of the
corner tree, an uprooted fir, 30 ins. diam., bearing a healed blaze
on one side; from the corner point, the original bearing trees,

An uprooted fir, 50 ins. diam., plainly blazed and healed,
the stump hole of which bears N. 76° E., 16 lks. dist.

A fir snag, 30 ins. diam., bears N. 69° W., 25 lks. dist.,
with scribe marks $\frac{1}{4}$ S BT visible on partly healed blaze.