

## Dependent Resurvey of a Portion of the N. Bdy. of T. 20 S., R. 9 W.

CHAINS	
11.80	Ravine, course N. 10° W.; asc. 90 ft. over NW. slope.
13.75	Spur, slopes N. 20° E.; desc. 450 ft. over E. slope, changing to SE.
28.15	Gold Creek, 20 lks. wide, course S. 5° W.; asc. 60 ft. over SW. slope.
30.20	Graded and blazed trail, bears N. 40° W. and S. 40° E.
30.65	Telephone line, bears N. 40° W. and S. 40° E.
32.60	Top of ascent on S. slope; desc. 45 ft. over SE. slope.
33.70	Creek, 12 lks. wide, course SW.; asc. 125 ft. over NW. slope.
38.52	The $\frac{1}{4}$ sec. cor. of sec. 36, T. 19 S., R. 9 W., determined from the original bearing trees, as follows:  A fir, 36 ins. diam., bears S. 37° E., 12 lks. dist., marked $\frac{1}{4}$ S BT on bark blaze.  The stump hole of an uprooted and rotted fir, 8 ins. diam., bears N. 70° W., 17 lks. dist., with no marks remaining on tree.  At the corner point  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \text{ S } 36$ 1953 from which new bearing trees,  A cedar, 8 ins. diam., bears N. 26 $\frac{1}{2}$ ° E., 11 lks. dist., marked $\frac{1}{4}$ S36 BT.  A fir, 50 ins. diam., bears N. 56° W., 78 lks. dist., marked $\frac{1}{4}$ S36 BT.  East, beginning new measurement.  Ascend 20 ft. over NW. slope.
1.24	The $\frac{1}{4}$ sec. cor. of sec. 1, determined from the original bearing trees, as follows:  A fir, 30 ins. diam., bears S. 13 $\frac{1}{2}$ ° E., 10 lks. dist., marked $\frac{1}{4}$ S BT on bark blaze.  A fir, 24 ins. diam., bears N. 29° W., 29 lks. dist., with faint scribe marks visible on badly scaled bark blaze.  At the corner point  Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \text{ S } 1$ 1953 from which new bearing trees,  A fir, 24 ins. diam., bears S. 55 $\frac{1}{4}$ ° E., 59 lks. dist., marked $\frac{1}{4}$ S1 BT.  A fir, 16 ins. diam., bears S. 69° W., 42 lks. dist., marked $\frac{1}{4}$ S1 BT.  S. 89° 29' E., beginning new measurement.