

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 12 ins. in the ground to solid rock, and in a mound of stone, to top, with brass cap marked

$\frac{1}{4}$ $\frac{S\ 25}{S\ 36}$
1954

from which new bearing trees,

A hemlock, 10 ins. diam., bears N. $43\frac{1}{4}^\circ$ W., 38 lks. dist., marked $\frac{1}{4}$ S25 BT.

A cedar, 13 ins. diam., bears S. $17\frac{1}{2}^\circ$ W., 47 lks. dist., marked $\frac{1}{4}$ S36 BT.

N. $87^\circ 18'$ E., beginning new measurement.

Descend 80 ft. over precipitous E. slope.

- 1.30 Ravine, course N. 20° E.; asc. 50 ft. over NW. slope.
- 3.25 Top of ascent on N. slope; desc. 115 ft. over broken NE. slope.
- 9.10 Dry bed of stream, 4 lks. wide, course N.; asc. 6 ft. along broken N. slope.
- 11.50 Ravine, course N.; desc. 28 ft. along broken N. slope.
- 21.65 Dry bed of stream, 4 lks. wide, course N.; asc. 100 ft. over broken NW. slope.
- 24.20 Spur, slopes N. 40° W.; asc. 100 ft. along broken N. slope.
- 28.60 Top of ascent on N. slope; desc. 40 ft. over NE. slope.
- 30.30 Ravine, course N. 20° W.; asc. 180 ft. over NW. slope.
- 34.20 Spur, slopes NE.; desc. 150 ft. over E. slope.
- 36.95 Ravine, course N. 30° E.; asc. 30 ft. over NW. slope, changing to broken N. slope.
- 39.90 Ravine, course N. 40° W.; asc. 120 ft. over W. slope.
- 42.40 Spur, slopes NW.; asc. 50 ft. along N. slope.
- 44.75 Spur, slopes N.; desc. 105 ft. over E. slope.
- 46.95 Head of ravine, course N. 30° E.; asc. 50 ft. over NW. slope.
- 49.84 Intersect the W. bdy. of sec. 30, T. 20 S., R. 8 W.

Point for the closing cor. of secs. 25 and 36, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., in a notch, 6 x 3 ins., chiseled 2 ins. in solid sandstone, and in a mound of stone, 8 ft. base, to top, with brass cap marked

T 20 S | T 20 S
CC $\frac{S\ 25}{S\ 36}$ | S 30
R 9 W | R 8 W
1954

from which