

## County Surveyor's Record, Douglas County, Oregon

21

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

## CHAINS

A fir, 14 ins. diam., bears N. 65° W., 29 lks. dist.,  
marked T20S R9W S25 CC BT.

A fir, 15 ins. diam., bears S. 54 $\frac{1}{4}$ ° W., 36 lks. dist.,  
marked T20S R9W S36 CC BT.

From this point the  $\frac{1}{4}$  sec. cor. on the W. bdy. of sec. 30, T. 20 S.,  
R. 8 W., bears N. 1° 27' E., 0.88 chs. dist., marked by a fir stub,  
14 ins. diam., marked and witnessed as described in the official  
record.

Land, mountainous. Soil, sandy and rocky clay loam. Timber, fir,  
hemlock, cedar, maple, alder, and yew. Undergrowth, vine maple,  
hazel, arrowwood, evergreen huckleberry, salmonberry, thimbleberry,  
and salal.

To complete the survey of sec. 36, I go to the cor. of secs. 30 and  
31, T. 20 S., R. 8 W., on the E. bdy. of sec. 36, which is monu-  
mented with an iron post, 2 ins. diam., 8 ins. above ground, firmly  
set, marked and witnessed as described in the official record, and  
run

S. 1°27' W., along the E. bdy. of sec. 36.

0.955 Point for the  $\frac{1}{4}$  sec. cor. of sec. 36 only, at midpoint on the E.  
bdy. of sec. 36.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground,  
with brass cap marked

$\frac{1}{4}$  S 36 |  
 1954

from which

An alder, 10 ins. diam., bears S. 46 $\frac{1}{2}$ ° W., 29 lks. dist.,  
marked  $\frac{1}{4}$  S36 BT.

An alder, 16 ins. diam., bears N. 39° W., 17 lks. dist.,  
marked  $\frac{1}{4}$  S36 BT.

The  $\frac{1}{4}$  sec. cor. is located on a SE. slope, 42 ft. lower than the  
cor. of secs. 30 and 31, T. 20 S., R. 8 W.

From the cor. of secs. 25, 26, 35, and 36.

N. 0° 18' W., bet. secs. 25 and 26.

Ascend 110 ft. over SE. slope, through heavy timber and dense  
undergrowth.

4.15 Ridge, bears N. 60° E. and S. 60° W.; desc. 350 ft. over steep,  
broken NW. slope.

13.60 Spur, slopes NW.; desc. 310 ft. over bluffy N. slope.

19.60 Left edge of Smith River, course S. 65° W.

21.10 Right edge of Smith River; asc. 20 ft. over bank facing S.

21.60 Top of bank, bears N. 65° E. and S. 65° W.; asc. 5 ft. over level  
bench.

25.95 Graded and blazed trail, bears NW. and SE., along edge of bench;  
asc. 165 ft. over SE. slope, changing to E. slope.

34.35 Ravine, course S. 35° E.; asc. 170 ft. over S. slope.