

## Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS  
40.43


The  $\frac{1}{4}$  sec. cor. of secs. 25 and 26, determined from the original bearing trees, as follows:

A fir, 62 ins. diam., bears N. 83° E., 45 lks. dist., with blaze opened and no marks remaining on charred face.

A fir, 50 ins. diam., bears N. 51° W., 20 lks. dist., with blaze opened and no marks remaining on charred face.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which new bearing trees,

A hemlock, 8 ins. diam., bears S. 76° E., 11 lks. dist., marked  $\frac{1}{4}$  S25 BT.

A hemlock, 8 ins. diam., bears S. 43° W., 49 lks. dist., marked  $\frac{1}{4}$  S26 BT.

The  $\frac{1}{4}$  sec. cor. is located on top of indistinct spur ridge, bears NE. and SW.

N. 0° 34' W., beginning new measurement.

Ascend 20 ft. over gradual SW. slope, changing to broken W. slope.

24.30 Branch, 1 lk. wide, course S. 80° W.; asc. 175 ft. over SW. slope.

32.55 Spur ridge, bears N. 75° E. and S. 75° W.; desc. 225 ft. over steep N. slope.

37.30 Branch, 3 lks. wide, course N. 85° W.; asc. 115 ft. over S. slope.

39.87 The cor. of secs. 23, 24, 25, and 26, determined from the remaining original bearing trees, as follows:


An uprooted cedar, 15 ins. diam., with blaze decayed, the stump hole of which bears N. 66° E., 50 lks. dist.

A cedar stump, 12 ins. diam., bears S. 43° E., 31 lks. dist., with decayed blaze on trunk found lying nearby.

A cedar snag, 16 ins. diam., bears N. 80 $\frac{1}{2}$ ° W., 47 lks. dist., with no marks remaining on burned blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which new bearing trees,

A fir, 15 ins. diam., bears N. 48 $\frac{1}{2}$ ° E., 25 lks. dist., marked T20S R9W S24 BT.