

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS  
27.20

Spur, slopes SE., curving to E.; desc. 650 ft. over NE. slope, changing to broken E. slope, near N. side of spur.

45.50

Edge of bench, bears NE. and SW.; desc. 48 ft. across bench, slopes gradually SE.

50.96

Graded and blazed trail, bears N. 50° E. and S. 50° W.

51.42

Intersect the W. bdy. of sec. 19, T. 20 S., R. 8 W.

Point for the closing cor. of secs. 24 and 25, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

|         |        |
|---------|--------|
| T 20 S  | T 20 S |
| CC S 24 | S 19   |
| S 25    |        |
| R 9 W   | R 8 W  |
|         | 1954   |

from which

A maple, 25 ins. diam., bears N. 25° W., 33 lks. dist., marked T20S R9W S24 CC BT.

A maple, 105 ins. diam., bears West, 172 lks. dist., marked T20S R9W S25 CC BT.

From this point the  $\frac{1}{4}$  sec. cor. on the W. bdy. of sec. 19, T. 20 S., R. 8 W., bears N. 0° 42' E., 0.78 chs. dist., monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, yew, and dogwood. Undergrowth, vine maple, hazel, arrowwood, salmonberry, rhododendron, huckleberry, salal, and sword fern.

To complete the survey of sec. 25, I go to the cor. of secs. 19 and 30, T. 20 S., R. 8 W., on the E. bdy. of sec. 25, which is monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record, and run

S. 0° 44' W., along the E. bdy. of sec. 25.

0.75

Point for the  $\frac{1}{4}$  sec. cor. of sec. 25 only, at midpoint on the E. bdy. of sec. 25.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

|                    |      |
|--------------------|------|
| $\frac{1}{4}$ S 25 |      |
|                    | 1954 |

from which

A fir, 25 ins. diam., bears S. 13° W., 10 lks. dist., marked  $\frac{1}{4}$  S25 BT.

A fir, 19 ins. diam., bears N. 85° 45' W., 24 lks. dist., marked  $\frac{1}{4}$  S25 BT.

From the cor. of secs. 23, 24, 25, and 26.

N. 3° 34' W., bet. secs. 23 and 24.