

County Surveyor's Record, Douglas County, Oregon

25

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

Ascend 95 ft. over S. slope, changing to SW. slope, through heavy timber and dense undergrowth.

3.65 Spur, slopes S. 80° W.; desc. 220 ft. over N. slope, changing to NW. slope.

8.70 Ravine, course S. 80° W.; asc. 100 ft. over SW. slope.

10.60 Spur, slopes SW.; desc. 200 ft. over NW. slope.


18.80 Dry bed of stream, 2 lks. wide, course NW.; desc. 30 ft. along W. slope.

21.00 Coldwater Creek, 5 lks. wide, course S. 30° W.; asc. 120 ft. over broken SE. slope.

31.50 Ravine, course S. 80° E.; asc. 345 ft. over steep S. slope, changing to broken SE. slope.

39.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A hemlock, 8 ins. diam., bears S. 60° E., 45 lks. dist., marked $\frac{1}{4}$ S24 BT.A hemlock, 8 ins. diam., bears S. 31° W., 58 lks. dist., marked $\frac{1}{4}$ S23 BT.

Ascend 50 ft. over SE. slope.

41.50 Spur, slopes NE.; desc. 180 ft. over N. slope.

45.00 Ravine, course N. 30° E.; desc. 80 ft. along E. slope, changing to NE. slope.

47.10 Branch, 1 lk. wide, course E.; asc. 250 ft. over S. slope.

52.90 Spur, slopes S. 50° E.; desc. 150 ft. over broken NE. slope.

59.10 Ravine, course S. 80° E.; asc. 220 ft. over SE. slope.

63.60 Spur, slopes S. 70° E.; desc. 130 ft. over NE. slope.

66.40 Ravine, course E.; asc. 260 ft. over SE. slope.

71.60 Spur, slopes S. 70° E.; desc. 400 ft. over precipitous N. slope, changing to NE. slope.

79.80 The cor. of secs. 13, 14, 23, and 24, determined from the original bearing trees, as follows:

A cedar, 24 ins. diam., bears N. 9 $\frac{1}{2}$ ° E., 84 lks. dist., plainly blazed and healed. (Record bearing, N. 6° E.)

An uprooted cedar, 72 ins. diam., with blaze buried, the stump hole of which bears S. 74° E., 19 lks. dist.

A vine maple, 6 ins. diam., bears S. 60° W., 55 lks. dist., with partial scribe marks remaining on blaze, which has been partly split off.