

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

- 63.10 Ravine, course NE.; asc. 80 ft. along steep N. slope.
- 71.00 Spur ridge, bears N. 50° E. and S. 50° W.; desc. 385 ft. over SE. slope.
- 82.30 Dry bed of stream, 3 lks. wide, course NE.; asc. 40 ft. over NW. slope.
- 84.20 Spur, slopes N. 20° E.; desc. 100 ft. over NE. slope.
- 87.00 Creek, 10 lks. wide, course SE.; asc. 15 ft. along S. slope.
- 90.65 Dry bed of stream, 2 lks. wide, course SW.; asc. 290 ft. over W. slope, changing to broken SW. slope.
- 97.89 Intersect the W. bdy. of sec. 18, T. 20 S., R. 8 W.

Point for the closing cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap marked

T 20 S	T 20 S
CC S 13	S 18
S 24	R 8 W
R 9 W	R 8 W
1954	

from which

A fir, 53 ins. diam., bears N. 63° W., 26 lks. dist., marked T20S R9W S13 CC BT.

A cedar, 25 ins. diam., bears S. 21° 45' W., 26 lks. dist., marked T20S R9W S24 CC BT.

From this point the $\frac{1}{4}$ sec. cor. on the W. bdy. of sec. 18, T. 20 S., R. 8 W., bears N. 0° 47' E., 1.36 chs. dist., monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

Land, mountainous. Soil, sandy and rocky clay loam. Timber, fir, hemlock, cedar, alder, and maple. Undergrowth, vine maple, hazel, arrowwood, evergreen huckleberry, salmonberry, thimbleberry, and rhododendron.

To complete the survey of sec. 24, I go to the cor. of secs. 18 and 19, T. 20 S., R. 8 W., on the E. bdy. of sec. 24, which is monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record, and run

S. 0° 42' W., along the E. bdy. of sec. 24.

- 1.58 Point for the $\frac{1}{4}$ sec. cor. of sec. 24 only, at midpoint on the E. bdy. of sec. 24.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 24	
1954	

from which

A hemlock, 10 ins. diam., bears S. 61° 45' W., 76 lks. dist., marked $\frac{1}{4}$ S24 BT.