

County Surveyor's Record, Douglas County, Oregon

12475

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

T 20 S | T 20 S
 CC $\frac{S}{S}$ $\frac{12}{13}$ | S 7
 R 9 W | R 8 W
 1954

from which

A fir, 36 ins. diam., bears N. 67° W., 69 lks. dist., marked T20S R9W S12 CC BT.

A fir, 36 ins. diam., bears S. 53 $\frac{1}{4}$ ° W., 30 lks. dist., marked T20S R9W S13 CC BT.

From this point the $\frac{1}{4}$ sec. cor. on the W. bdy. of sec. 7, T. 20 S., R. 8 W., bears N. 0° 34' E., 1.67 chs. dist., monumented with an iron post, 1 in. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.

The closing cor. is located on back of spur, slopes NW.

Land, mountainous. Soil, sandy and rocky clay loam. Timber, fir, cedar, hemlock, maple, alder, madrona, chinquapin, yew, and dogwood. Undergrowth, vine maple, evergreen huckleberry, salmonberry, red huckleberry, rhododendron, hazel, arrowwood, ceanothus, manzanita, thimbleberry, wild cherry, sword fern, Oregon grape, and salal.

To complete the survey of sec. 13, I go to the cor. of secs. 7 and 18, T. 20 S., R. 8 W., on the E. bdy. of sec. 13, which is monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record, and run

S. 0° 08' W., along the E. bdy. of sec. 13.

2.37 Point for the $\frac{1}{4}$ sec. cor. of sec. 13 only, at midpoint on the E. bdy. of sec. 13.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 13 |
 1954

from which

A hemlock, 35 ins. diam., bears S. 57° 45' W., 25 lks. dist., marked $\frac{1}{4}$ S13 BT.

A hemlock, 38 ins. diam., bears N. 16° 45' W., 81 lks. dist., marked $\frac{1}{4}$ S13 BT.

From the cor. of secs. 11, 12, 13, and 14.

N. 0° 06' W., bet. secs. 11 and 12.

Ascend 80 ft. along W. slope, changing to SW. slope, through heavy timber and dense undergrowth. Occasional fir trees have been logged approximately 30 to 40 years ago on both sides of line.

4.20 Spur, slopes N. 75° W.; desc. 135 ft. over NE. slope.

7.25 Ravine, course N. 50° W.; asc. 100 ft. over W. slope.

14.25 Spur, slopes N. 15° W.; desc. 350 ft. over steep N. slope.

20.40 Branch, 4 lks. wide, course W.; asc. 140 ft. over S. slope.