

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS 25.00	Spur, slopes S. 80° W.; desc. 145 ft. over NW. slope.
32.10	Enter bottom land; edge bears NE. and SW.; asc. slightly along bottom.
39.21	The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, determined from the original bearing trees, as follows: A fir snag, 40 ins. diam., bears S. 28° E., 54 lks. dist., with only the marks BT remaining on bark blaze. A fir, 60 ins. diam., bears S. 9° W., 56 lks. dist., marked $\frac{1}{4}$ S BT on bark blaze. At the corner point Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked <div style="text-align: center;"> $\frac{1}{4}$ S 11 S 12 1953 </div> from which new bearing trees, A fir, 26 ins. diam., bears S. 72 $\frac{1}{2}$ ° E., 47 lks. dist., marked $\frac{1}{4}$ S12 BT. A cedar, 21 ins. diam., bears S. 33 $\frac{1}{2}$ ° W., 20 lks. dist., marked $\frac{1}{4}$ S11 BT. The $\frac{1}{4}$ sec. cor. is located at the S. side of a fir stump, 8 ft. diam. <hr style="width: 20%; margin: 0 auto;"/> N. 0° 13' W., beginning new measurement. Descend 5 ft. along bottom.
4.00	Truck trail and telephone line, bear N. 5° E. on curve to NE. and S. 5° W.
8.00	Left bank of West Fork of Smith River, course S. 20° W.
10.50	Right bank of West Fork of Smith River; asc. 140 ft. along E. slope, changing to SE. slope.
11.80	Preliminary center line of access road under construction, bears N. 20° E. and S. 20° W.
18.50	Change of slope; asc. 250 ft. over S. slope.
23.70	Spur, slopes E.; desc. 140 ft. over NE. slope.
26.75	Ravine, course N. 70° E.; desc. 80 ft. along broken E. slope.
32.20	Branch, 2 lks. wide, course E.; asc. 70 ft. over SE. slope.
36.80	Top of ascent on flat spur, slopes N. 25° E.; desc. 25 ft. over gradual NW. slope.
39.98	The cor. of secs. 1, 2, 11, and 12, determined at record bearing and distance from each of the original bearing trees, as follows: A fir, 40 ins. diam., bears N. 88° E., 15 lks. dist., marked T20S R9W S1 BT on bark blaze. A vine maple, 8 ins. diam., bears S. 32° E., 18 lks. dist., with scribe marks visible on partly healed blaze.