


Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

- 6.75 Scare Creek, 20 lks. wide, course N. 30° W.; asc. 120 ft. along broken W. slope.
- 20.25 Spur, slopes N. 40° W.; desc. 140 ft. over NE. slope.
- 23.80 Branch, 5 lks. wide, course NW.; asc. 180 ft. along broken W. slope.
- 40.82 Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked



*FD: OK L.D. ROBERTS  
2/19/84 C.S. 58/280  
MRL-26*

from which


A fir, 7 ins. diam., bears S. 16 $\frac{1}{2}$ ° E., 24 $\frac{1}{2}$  lks. dist., marked  $\frac{1}{4}$  S35 BT.

A fir, 8 ins. diam., bears N. 41° W., 3 lks. dist., marked  $\frac{1}{4}$  S34 BT.

Ascend 5 ft. along broken W. slope.

- 41.30 Top of ascent on W. slope; desc. 80 ft. over NW. slope.
- 44.95 Ravine, course W.; desc. 20 ft. along broken W. slope.
- 49.15 Ravine, course W.; asc. 400 ft. over broken SW. slope.
- 62.20 Ridge, the divide bet. Scare Creek and Smith River, bears N. 60° W. and S. 60° E.; desc. 590 ft. over broken N. slope.
- 74.25 Left bank of Smith River, course S. 80° W.
- 75.90 Right bank of Smith River; asc. 128 ft. over general S. slope.
- 77.10 Graded and blazed trail, and preliminary center line of access road under construction, bear E. and W.
- 81.64 Point for the cor. of secs. 26, 27, 34, and 35, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked



from which

A fir, 24 ins. diam., bears N. 83° 45' E., 43 lks. dist., marked T20S R9W S26 BT.

A fir, 18 ins. diam., bears S. 83° 45' E., 38 lks. dist., marked T20S R9W S35 BT.

A fir, 14 ins. diam., bears S. 11 $\frac{1}{4}$ ° W., 87 lks. dist., marked T20S R9W S34 BT.

A fir, 14 ins. diam., bears N. 45 $\frac{1}{4}$ ° W., 76 lks. dist., marked T20S R9W S27 BT.