

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, and dogwood. Undergrowth, vine maple, salmon-berry, hazel, rhododendron, evergreen huckleberry, red huckleberry, salal, sword fern, and Oregon grape.

From the cor. of secs. 25, 26, 35, and 36.

S. 88° 27' W., bet. secs. 26 and 35.

Descend 30 ft. along S. slope, through heavy timber and dense undergrowth.

- 11.00 Ridge, bears N. 70° E. and S. 70° W.; desc. 520 ft. over broken NW. slope.
- 34.00 Dry bed of stream, 1 lk. wide, course N.; desc. 20 ft. across bottom.
- 37.00 Left edge of Smith River, course SW.
- 39.30 Right edge of Smith River; asc. 25 ft. across bottom.
- 41.10 Graded and blazed trail, bears N. 65° E. and S. 65° W.
- 43.50 Branch, 2 lks. wide, course S.; asc. 6 ft. over bottom.
- 45.28 The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, located by reference to calls of the original field notes and the remains of an original bearing tree, as follows:
- A sawed fir stump, 72 ins. diam., bears N. 79° E., 545 lks. dist., with no marks remaining on decayed blaze; this is the only old growth tree in the immediate vicinity.
- The ruins of Compton's cabin, consisting of fire place stones, broken crockery, and a few decaying cedar boards, bears East, 75 lks. dist.
- A pile of rotting timbers, evidently the remains of Compton's barn, occupies the approximate position mentioned in the field notes of the original survey.
- At the corner point
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked
- $$\begin{array}{r} \frac{1}{4} \text{ S } 26 \\ \frac{1}{4} \text{ S } 35 \\ 1953 \end{array}$$
- from which new bearing trees,
- A fir, 28 ins. diam., bears N. 45 $\frac{1}{2}$ ° E., 9 lks. dist., marked $\frac{1}{4}$ S26 BT.
- A fir, 18 ins. diam., bears S. 36° 45' W., 12 lks. dist., marked $\frac{1}{4}$ S35 BT.
-
- S. 86° 58' W., beginning new measurement.
- Descend 5 ft. over bottom land.
- 15.50 Graded and blazed trail, and preliminary center line of access road under construction, bear S. 83° E. and S. 87° W.; thence along trail.
- 18.80 Leave trail, bears N. 87° E. and S. 85° W.