

County Surveyor's Record, Douglas County, Oregon

42

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

$$\begin{array}{c} \frac{1}{4} \\ | \\ \text{S } 22 \text{ } | \text{ } \text{S } 23 \\ | \\ 1953 \end{array}$$

from which

A double maple, 25 ins. diam., bears S. $46\frac{1}{2}^{\circ}$ E., 70 lks. dist., marked $\frac{1}{4}$ S23 BT.

A fir, 10 ins. diam., bears N. $21\frac{1}{2}^{\circ}$ W., 118 lks. dist., marked $\frac{1}{4}$ S22 BT.

Ascend 31 ft. over SW. slope, changing to W. slope.

- 40.45 A cedar, 26 ins. diam., on line, marked with two hacks each on N. and S. sides.
- 42.70 Intermittent branch, 1 lk. wide, course S. 10° W.; asc. 287 ft. over SE. slope, changing to E. slope.
- 50.80 Head of ravine, course SE.; asc. 226 ft. over S. slope.
- 56.70 Ridge, the divide bet. Smith River and West Fork of Smith River, bears NE. and S. 80° W.; desc. 180 ft. over broken NW. slope, changing to W. slope.
- 64.55 Spur, slopes N. 50° W.; desc. 138 ft. over N. slope.
- 67.70 Head of ravine, course W.; asc. 290 ft. over SW. slope.
- 78.20 Spur ridge, bears NW. and SE.; desc. 30 ft. over NE. slope.
- 79.22 The cor. of secs. 14, 15, 22 and 23, determined at record bearing and distance from each of the remaining original bearing trees, as follows:
- A fir, 50 ins. diam., bears N. 87° E., 16 lks. dist., marked T20S R9W S14 BT. on bark blaze.
- A cedar stump, 35 ins. diam., bears S. 51° W., 14 lks. dist., with partial scribe marks in negative visible on inside surface of hollow shell.
- A cedar, 36 ins. diam., bears N. 6° W., 57 lks. dist., plainly blazed and healed.
- At the corner point
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked
- $$\begin{array}{c} \text{T20S R9W} \\ \text{S } 15 \text{ } | \text{ } \text{S } 14 \\ \text{S } 22 \text{ } | \text{ } \text{S } 23 \\ 1953 \end{array}$$
- From which new bearing trees,
- A cedar, 23 ins. diam., bears N. $55\frac{1}{2}^{\circ}$ E., 27 lks. dist., marked T20S R9W S14 BT.
- A cedar, 24 ins. diam., bears S. 38° E., 91 lks. dist., marked T20S R9W S23 BT.
- A fir, 35 ins. diam., bears S. $16\frac{1}{4}^{\circ}$ W., 21 lks. dist., marked T20S R9W S22 BT.
- A cedar, 25 ins. diam., bears N. 17° W., 67 lks. dist., marked T20S R9W S15 BT.