

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.


CHAINS

A fir stump, 24 ins. diam., bears N. 31° E., 16 lks. dist., with no marks remaining. (Mensch bearing tree.)

A fir snag, 24 ins. diam., bears S. 69° E., 24 lks. dist., with no marks remaining. (Thiel bearing tree.)

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which new bearing trees,

A fir, 40 ins. diam., bears S. 25° E., 49 lks. dist., marked $\frac{1}{4}$ S11 BT.


A fir, 50 ins. diam., bears N. 50 $\frac{1}{2}$ ° W., 77 lks. dist., marked $\frac{1}{4}$ S10 BT.

Deposit the old iron post alongside the new one.

N. 0° 22' E., beginning new measurement.

Ascend 110 ft. over SW. slope.

- 3.05 Spur ridge, bears N. 80° E. and S. 80° W.; desc. 45 ft. slope.
- 6.40 Spur, slopes N. 35° E.; desc. 360 ft. over NW. slope.
- 14.80 Foot of slope, bears E. and W.; desc. 10 ft. over bottom.
- 15.50 Branch, 2 lks. wide, course S. 80° E., at junction of forks from N. 80° W. and S. 25° W.; asc. 320 ft. over SE. slope.
- 22.40 Spur, slopes E.; desc. 330 ft. over NE. slope.
- 29.30 Branch, 3 lks. wide, course S. 80° E.; asc. 360 ft. over S. slope.
- 37.50 The cor. of secs. 2, 3, 10 and 11, remonumented by Fred Mensch, in 1921, with an iron post, 2 ins. diam., 16 ins. above ground, firmly set, with brass cap marked



from which

A vine maple, 6 ins. diam., bears N. 34° E., 28 lks. dist., with partial scribe marks visible on nearly healed blaze. (Mensch bearing tree.)

An uprooted fir, 44 ins. diam., plainly blazed and healed, the stump hole of which bears S. 86° W., 27 lks. dist. (Thiel bearing tree.)

An uprooted fir, 38 ins. diam., plainly blazed and healed, the stump hole of which bears N. 42° W., 42 lks. dist. (Thiel bearing tree.)