

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

A fir, 45 ins. diam., bears N. $72\frac{1}{2}^\circ$ W., 66 lks. dist., marked T20S R9W S16 BT on bark blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 9 W
S 16 | S 15
S 21 | S 22
1953

*Fd. O.K.
by:
Roberts
1982
M 90-31*

from which new bearing trees,

A fir, 48 ins. diam., bears N. $52\frac{1}{2}^\circ$ E., 93 lks. dist., marked T20S R9W S15 BT.

A fir, 48 ins. diam., bears S. 32° E., 106 lks. dist., marked T20S R9W S22 BT.

*Destroyed by Road Construction
Per L. Roberts M*

A fir, 36 ins. diam., bears S. 87° W., 225 lks. dist., marked T20S R9W S21 BT.

Land, mountainous and rolling. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, alder, chinquapin, and madrona. Undergrowth, vine maple, hazel, salmonberry, evergreen and red huckleberry, arrowwood, and salal.

From the cor. of secs. 14, 15, 22, and 23.

N. $89^\circ 54'$ W., bet. secs. 15 and 22.

Ascend 30 ft. over NE. slope, through heavy timber and dense undergrowth.

1.50 Ridge, bears NW. and SE.; desc. 290 ft. over SW. slope, changing to S. slope.

13.50 Spur, slopes S. 60° W.; desc. 350 ft. over broken W. slope, changing to SW. slope.

21.00 Branch, 4 lks. wide, course N. 15° W.; asc. 290 ft. over NE. slope.

26.70 Spur, slopes N.; desc. 180 ft. over W. slope.

30.45 Branch, 4 lks. wide, course N. 10° E., at forks from S. 20° E. and S. 55° W.; asc. 160 ft. over SE. slope.

34.70 Spur, slopes N. 50° E.; desc. 20 ft. along N. slope.

36.45 Spur, slopes NW.; desc. 110 ft. over NW. slope.

39.35 Ravine, course N.; asc. 7 ft. over NE. slope.

39.74 The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at record bearing and distance from each of the original bearing trees, as follows:

A fir, 50 ins. diam., bears N. 54° W., 50 lks. dist., marked $\frac{1}{4}$ S on bark blaze.

A rotted cedar stump, 24 ins. diam., bears S. $49\frac{1}{2}^\circ$ E., 42 lks. dist., with no marks remaining.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked