

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS	
2.15	Telephone line, along edge of timber, bears N. and S.; thence across opening of grass and fern.
7.00	Truck trail, bears N. 10° W. and S. 10° E., along W. edge of opening; re-enter heavy timber and dense undergrowth.
10.10	West Fork of Smith River, 45 lks. wide, course S. 55° E.; asc. 15 ft. over bank, slopes NE.
10.60	Access road under construction, bears N. 55° W. and S. 55° E.; asc. 300 ft. over NE. slope.
17.95	Spur ridge, bears N. 20° W. and S. 20° E.; desc. 235 ft. over SW. slope.
24.40	Branch, 2 lks. wide, in gravel bed, 15 lks. wide, course S.; asc. 60 ft. over E. slope.
27.20	Spur, slopes S. 50° E.; desc. 25 ft. along S. slope.
31.00	Dry bed of stream, 2 lks. wide, course S. 80° E.; asc. 140 ft. over NE. slope.
38.20	Top of ascent on N. slope; desc. 30 ft. over NW. slope.
39.40	Dry bed of stream, 2 lks. wide, course N. 30° E.; asc. 10 ft. over E. slope.
39.65	The $\frac{1}{4}$ sec. cor. of secs. 10 and 15, remonumented by Fred Mensch, in 1921, with an iron post, 1 in. diam., 8 ins. above ground, firmly set, properly marked but rusted nearly through, from which  An uprooted cedar, 12 ins. diam., with blaze decayed, the stump hole of which bears N. 31 $\frac{1}{2}$ ° E., 31 lks. dist. (Original B. T.)  A maple, 12 ins. diam., bears S. 87 $\frac{1}{2}$ ° W., 66 lks. dist., with blaze healed. (Original B. T.)  At the corner point  In place of the rusted iron post, set a new iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked  $\frac{1}{4}$ $\frac{S}{S}$ $\frac{10}{15}$ 1954  from which a new bearing tree,  A fir, 50 ins. diam., bears N. 28 $\frac{1}{2}$ ° W., 39 lks. dist., marked $\frac{1}{4}$ S10 BT.  Deposit the old iron post alongside the new one.  S. 89° 31' W., beginning new measurement.  Ascend 230 ft. over E. slope, changing to NE. slope.
6.10	Spur, slopes N. 15° E.; desc. 60 ft. over NW. slope.
9.60	Branch, 1 lk. wide, course NE.; asc. 460 ft. over E. slope, changing to NE. slope.
22.75	Spur ridge, bears NW. and SE.; desc. 125 ft. over broken SW. slope.
30.95	Head of ravine, course S. 10° E.; asc. 190 ft. over SE. slope, changing to S. slope.

Fd. by  
LES  
2/25/83  
M 93-63  
Roberts