

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

- 0.46 A cedar, 66 ins. diam., on line, marked with blazes of the age of the Thiel survey on N. and S. sides.
- 2.23 Dry bed of stream, 4 lks. wide, course E.; asc. 175 ft. over SE. slope.
- 11.88 Junction of spurs from S. 50° W., slope North and N. 30° E.; desc. 90 ft. along spur.
- 14.50 End of spur; desc. 280 ft. over precipitous N. slope.
- 18.67 Dry bed of a stream, 4 lks. wide, course N. 70° E.; asc. 128 ft. over SE. slope.
- 22.42 Spur, slopes E.; desc. 324 ft. over NE. slope.
- 30.20 Thiel's line tree, a cedar, 36 ins. diam., marked with two hacks each, on N. and S. sides.
- 33.50 Left bank of Smith River, course N. 22° W., on bend to NW.
- 37.50 Right bank of Smith River; asc. 23 ft. over bottom land.
- 40.36 Access road, under construction, 45 lks. wide, bears N. 33° W. and S. 33° E.
- 40.44 The cor. of secs. 28, 29, 32, and 33, falls in roadway, determined at the record bearing and distance from each of the remaining original bearing trees, as follows:

A fir stump, 72 ins. diam., bears N. 25° 45' E., 126 lks. dist., with partly burned and decayed blaze facing corner.

A cedar stump, 84 ins. diam., bears S. 51° 45' E., 51 lks. dist., with no marks remaining on badly decayed face of old blaze. This stump has now been removed during clearing operations for access road.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 48 ins. in clay sub-grade of access road, with brass cap marked

T 20 S R 9 W			
S 29		S 28	
S 32		S 33	
1953			

from which new bearing trees and reference monuments,

A fir, 40 ins. diam., bears N. 44 $\frac{1}{4}$ ° E., 122 lks. dist., marked T20S R9W S28 BT.

An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears N. 45° E., 90 lks. dist., with brass cap marked T20S R9W S28 RM 1953 and an arrow pointing to the corner.

A fir, 38 ins. diam., bears S. 73 $\frac{1}{2}$ ° E., 106 lks. dist., marked T20S R9W S33 BT.

An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S. 45° W., 90 lks. dist., with brass cap marked T20S R9W S32 RM 1953 and an arrow pointing to the corner.

A fir, 28 ins. diam., bears S. 50° W., 83 lks. dist., marked T20S R9W S32 BT.