

## Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

## CHAINS

- 5.05 Graded dirt road, bears N.  $16\frac{1}{2}^{\circ}$  W. and S.  $16\frac{1}{2}^{\circ}$  E., winding.
- 12.70 Head of ravine, course S.; asc. 5 ft. along gradual S. slope of bench.
- 15.10 Leave bench; edge bears N. and S.; desc. 280 ft. over steep W. slope.
- 20.65 Rachel Creek, 5 lks. wide, in gravel bed, 20 lks. wide, course S., on bend to S.  $30^{\circ}$  W.; asc. 220 ft. over SE. slope.
- 26.60 Spur, slopes S.; desc. 320 ft. over SW. slope.
- 40.85 Enter roadway, bears N.  $33^{\circ}$  W. and S.  $33^{\circ}$  E.
- 41.11 The cor. of secs. 28, 29, 32, and 33.

Land, mountainous and rolling. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, and alder. Undergrowth, vine maple, hazel, evergreen and red huckleberry, rhododendron, ceanothus, manzanita, arrowwood, salmonberry, and salal.

N.  $0^{\circ} 25'$  E., bet. secs. 28 and 29.

Across roadway.

- 0.35 Edge of access road, under construction, bears N.  $33^{\circ}$  W. and S.  $33^{\circ}$  E.; asc. 10 ft. over bottom land through clearing.
- 1.70 Old road, unimproved, bears NW. on curve to N.  $60^{\circ}$  W. and SE.; asc. 36 ft. over bottom land, through heavy timber and dense undergrowth.
- 9.47 Spring branch, 2 lks. wide, course W.; asc. 33 ft. over bench sloping SW., through grassy openings.
- 13.75 Leave bench; edge bears NW. and SE.; asc. 56 ft. over SW. slope.
- 16.40 Spur, slopes W.; thence along general W. slope.
- 17.80 Branch, 3 lks. wide, course S.  $50^{\circ}$  W.; asc. 87 ft. over S. slope.
- 19.60 Spur, slopes S.  $10^{\circ}$  W.; asc. 290 ft. over broken SW. slope, through heavy young timber and dense undergrowth.
- 30.50 Sharply defined spur, slopes S.  $35^{\circ}$  W.; desc. 135 ft. over NW. slope.
- 35.40 Branch, 4 lks. wide, course S.  $80^{\circ}$  W.; asc. 126 ft. over SW. slope.
- 40.71 The  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, at record bearing and distance from each of the original bearing trees, as follows:
- A fir stump, 66 ins. diam., bears N.  $45^{\circ}$  E., 5 lks. dist., with axe marks remaining around decayed face of old blaze. (Appears to have been dead when marked.)
- A rotten fir stump, 40 ins. diam., bears S.  $45^{\circ}$  W., 4 lks. dist., with no marks remaining.
- At the corner point
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

