

County Surveyor's Record, Douglas County, Oregon
65

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

from which new bearing trees,

A fir, 28 ins. diam., bears S. 73° 45' E., 91 lks. dist., marked $\frac{1}{4}$ S28 BT.

A fir, 8 ins. diam., bears N. 76 $\frac{1}{4}$ ° W., 28 lks. dist., marked $\frac{1}{4}$ S29 BT.

N. 10° 38' E., beginning new measurement.

Ascend 272 ft. over gradual SW. slope, changing to W. slope.

10.70 Top of ascent on indistinct spur, slopes W.; desc. 121 ft. over NW. slope, changing to N. slope.

15.00 Ravine, course W.; asc. 22 ft. over SW. slope.

15.85 Small spur, slopes S. 80° W.; desc. 23 ft. over NW. slope.

18.00 Foot of descent on W. slope; asc. 67 ft. over SW. slope.

19.50 Spur, slopes W.; desc. 115 ft. over NW. slope.

23.00 Ravine, course N. 80° W.; asc. 80 ft. over SW. slope.

25.50 Spur, slopes N. 70° W.; desc. 80 ft. over NW. slope.

28.50 Ravine, course N. 60° W.; asc. 100 ft. over SW. slope.

32.60 Top of ascent on W. slope; desc. 200 ft. over NW. slope.

40.20 Ravine, course S. 75° W.; asc. 160 ft. over SW. slope.

44.20 Spur, slopes W.; desc. 10 ft. over NW. slope.

45.00 The cor. of secs. 20, 21, 28, and 29, perpetuated with an iron pipe, 4 ft. long, 2 ins. diam., fallen over and found lying near the corner point, with iron pipe cap marked

20 21
T 20 S R 9 W
29 28

from which the original bearing trees, which agree with the record,

A fir, 52 ins. diam., bears N. 24° E., 60 lks. dist., with no marks remaining on badly scaled bark blaze. I reblaze this tree below the original blaze and mark T20S R9W S21 BT.

A rotten fir stump, 36 ins. diam., bears S. 68° E., 54 lks. with axe marks in bark found lying at base.

A fir snag, 18 ins. diam., bears S. 64° W., 41 lks. dist., with no marks remaining on burned blaze.

A double fir stump, 20 ins. diam., bears N. 34 $\frac{1}{2}$ ° W., 55 lks. dist., sawed off below blaze when larger trunk of tree, 50 ins. diam., was logged. I open pitchy slab lying beside stump and uncover the scribe marks T20S R9W S20 BT.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked

T 20 S R 9 W
S 20 | S 21
S 29 | S 28
1953

Fd. O.K.
by: *LES Roberts*
Dec. 1982
M 90-31
10/10/84
e.s. 58/237