

County Surveyor's Record, Douglas County, Oregon  
66

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

from which new bearing trees,

A fir, 8 ins. diam., bears S.  $27\frac{1}{4}^{\circ}$  E., 48 lks. dist.,  
marked T20S R9W S28 BT.

A fir, 14 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  W., 77 lks. dist.,  
marked T20S R9W S29 BT.

A fir, 26 ins. diam., bears N.  $1^{\circ} 45'$  W., 82 lks. dist.,  
marked T20S R9W S20 BT.

Reset the iron pipe, 18 ins. in the ground, alongside the iron post.

Land, mountainous and rolling. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, and maple; mostly reproduction. Undergrowth, vine maple, salmonberry, hazel, rhododendron, evergreen huckleberry, arrowwood, salal, and bracken.

From the cor. of secs. 21, 22, 27, and 28.

N.  $89^{\circ} 12'$  W., bet. secs. 21 and 28.

Ascend 32 ft. over NE. slope, through heavy timber and dense undergrowth.

2.00 Spur, slopes N.  $10^{\circ}$  W.; desc. 258 ft. over W. slope.

2.21 A fir, 14 ins. diam., on line, marked with two notches each on E. and W. sides.

9.63 Disused shake cabin, bears N.  $47^{\circ}$  W.

12.14 Same cabin, bears N.  $10^{\circ}$  E.; a graded and blazed trail and telephone line, bear N.  $10^{\circ}$  E. and S.  $10^{\circ}$  W.

14.67 West Fork of Smith River, 86 lks. wide, course S.  $4^{\circ}$  W.; asc. 600 ft. over broken E. slope.

15.50 Truck trail and access road under construction, bear N. and S.

36.50 Ridge and graded dirt road, bear N.  $10^{\circ}$  E. and S.  $10^{\circ}$  W.; desc. 140 ft. over W. slope.

39.00 Rachel Creek, 5 lks. wide, course S.  $15^{\circ}$  W.; asc. 31 ft. over E. slope.

40.49 The  $\frac{1}{4}$  sec. cor. of secs. 21 and 28, at record bearing and distance from each of the original bearing trees, as follows:

An alder, 28 ins. diam., bears N.  $86\frac{1}{2}^{\circ}$  E., 63 lks. dist., with partial scribe marks visible on decayed face of partly healed blaze.

A double maple, 70 ins. diam., bears S.  $70^{\circ}$  W., 50 lks. dist., with blaze healed.

At the corner point

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S 21  
S 28  
1953

from which a new bearing tree,

*Fl. OK.*  
*by:*  
*Les Roberts*  
*Dec. 1982*  
*90-31*  
*M 10/10/84*  
*C.S. 58/237*