

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS The $\frac{1}{4}$ sec. cor. falls at a junction of spurs, from E., slope NW. and SW.

Descend 170 ft. over NW. slope.

43.80 Ravine, course N. 60° W.; asc. 50 ft. over SW. slope.

47.00 Top of ascent on W. slope; desc. 110 ft. over NW. slope.

49.20 Ravine, course S. 60° W.; asc. 210 ft. over S. slope.

53.75 Spur, slopes S. 60° W.; desc. 130 ft. over NW. slope.

57.35 Ravine, course S. 75° W.; asc. 230 ft. over SW. slope, changing to W. slope.

62.28 Disused graded trail, bears N. 68 $\frac{1}{4}$ ° W. and S. 68 $\frac{1}{4}$ ° E.

66.35 Ridge, the divide bet. Johnson Creek and Coon Creek, bears N. 15° W. and S. 15° E.; desc. 50 ft. over NE. slope.

67.85 Foot of descent on E. slope; asc. 40 ft. over SE. slope.

71.65 Spur ridge, bears NE. and SW.; desc. 58 ft. over NW. slope.

74.75 Spur, slopes steeply N. 25° W.; desc. 221 ft. over precipitous NE. slope.

78.75 Ravine, course N. 15° W.; desc. 13 ft. along broken W. slope.

79.56 The cor. of secs. 16, 17, 20, and 21, monumented with a sandstone, 24 x 18 x 5 ins., loosely set 10 ins. in the ground, marked with 1 groove on S. face; alongside of which has been driven an iron pipe, 4 ft. long, 2 ins. diam., 12 ins. in the ground, with iron pipe cap marked

17 16
T 20 S R 9 W
20 21

from the sandstone, the original bearing trees,

A fir, 44 ins. diam., bears N. 28° E., 61 lks. dist., marked T20S R9W S16 BT on bark blaze. (Record distance, 54 lks.)

A dead fir, 32 ins. diam., bears S. 76° E., 28 lks. dist., marked T20S R9W S21 BT on bark blaze. (Record distance, 25 lks.)

A dead fir, 50 ins. diam., bears S. 9° W., 14 lks. dist., plainly blazed and healed. (Record distance, 13 lks.)

The original NW. bearing tree has been uprooted, and occupies the approximate record position, with traces of scribe marks visible on badly scaled bark blaze.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T 20 S R 9 W
S 17 | S 16
S 20 | S 21
1953

from which new bearing trees,

A fir, 30 ins. diam., bears S. 52° 45' E., 106 lks. dist., marked T20S R9W S21 BT.

A fir, 25 ins. diam., bears S. 70° W., 140 lks. dist., marked T20S R9W S20 BT.

Handwritten:
Fd. OK. by:
Les Roberts
Dec. 19 82
M 90-31