

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.


CHAINS

32.80 Branch, 1 lk. wide, course S. 40° E.; asc. 340 ft. over S. slope.

33.45 Barbed wire fence, bears NW. and SE.

41.87 Point for the $\frac{1}{4}$ sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 22 ins. diam., bears N. 34° E., 9 lks. dist., marked $\frac{1}{4}$ S32 BT.

A fir, 29 ins. diam., bears N. 58 $\frac{1}{2}$ ° W., 23 lks. dist., marked $\frac{1}{4}$ S31 BT.

Ascend 40 ft. over S. slope.

43.00 Spur, slopes SW.; desc. 40 ft. along W. slope.

46.40 Head of ravine, course S. 75° W.; asc. 160 ft. over broken SW. slope.

57.40 Top of ascent on W. slope; desc. 220 ft. over NW. slope.

62.00 Branch, 1 lk. wide, course N. 60° W.; desc. 10 ft. along broken W. slope.

65.10 Ravine, course S. 65° W.; asc. 25 ft. over S. slope.

66.10 Spur, slopes S. 80° W.; desc. 330 ft. over broken NW. slope.

78.10 Intermittent branch, 3 lks. wide, course W.; asc. 37 ft. along broken W. slope.

83.74 The cor. of secs. 29, 30, 31, and 32, determined from the original bearing trees, as follows:


A sawed fir stump, 44 ins. diam., bears N. 22 $\frac{1}{2}$ ° E., 34 $\frac{1}{2}$ lks. dist., marked R9W on exposed portion of blaze. (Record distance, 33 lks.)

A sawed fir stump, 40 ins. diam., bears S. 63 $\frac{1}{2}$ ° E., 60 lks. dist., plainly blazed and healed. (Record distance, 58 lks.)

A sawed fir stump, 50 ins. diam., bears S. 36° W., 16 lks. dist., marked BT in negative on overgrowth. (Record distance, 15 lks.)

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which new bearing trees,

A fir, 16 ins. diam., bears N. 23° 45' E., 56 lks. dist., marked T20S R9W S29 BT.