

County Surveyor's Record, Douglas County, Oregon

75

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS	<p>A fir, 54 ins. diam., bears N. 25° W., 52 lks. dist., marked $\frac{1}{4}$ S30 BT.</p> <p>A fir, 24 ins. diam., bears S. 12° W., 113 lks. dist., marked $\frac{1}{4}$ S31 BT.</p> <p>Ascend 180 ft. over SE. slope.</p>
44.20	Spur, slopes S. 5° E.; desc. 300 ft. over broken SW. slope.
52.20	Branch, 2 lks. wide, course S., gradually bending to SE.; asc. 550 ft. over steep E. slope, changing to gentle E. slope.
68.00	Ridge, bears N. and S.; about $1\frac{1}{2}$ chs. S. of line, a sharp spur slopes S. 60° W. and ridge turns to SE.; desc. 500 ft. over general W. slope, changing to NW. slope.
81.20	<p>The cor. of secs. 19, 30, 31, and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.</p> <p>Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, and maple. Undergrowth, vine maple, salmonberry, hazel, arrowwood, rhododendron, evergreen and red huckleberry, salal, sword fern, and bracken.</p>
	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 1° 13' E., bet. secs. 29 and 30.</p> <p>Descend 30 ft. along W. slope, changing to NW. slope.</p>
1.40	Branch, 3 lks. wide, course W.; a $\frac{3}{4}$ in. iron pipe water line, bears E. and W. along stream; asc. 70 ft. over gradual SW. slope.
12.70	Top of ascent on W. slope; desc. 90 ft. along W. edge of bench on gradual W. slope, changing to NW. slope.
22.90	Edge of bottom, bears NE. and SW.; desc. 7 ft. across bottom.
26.85	Dry bed of a stream, 3 lks. wide, course N. 60° W.; desc. 8 ft. across bottom.
28.75	Left bank of Smith River, course SW.
32.50	Right bank of Smith River; asc. 93 ft. over SE. slope.
33.70	Graded dirt road, bears NE. and SW.
36.30	Top of ascent on E. slope; desc. 72 ft. over precipitous NE. slope.
38.60	Bear Creek, 12 lks. wide, course SE.; asc. 43 ft. over SW. slope.
40.30	Top of ascent on W. slope; desc. 13 ft. over NW. slope.
41.00	<p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at record bearing and distance from each of the original bearing trees, as follows:</p> <p style="padding-left: 40px;">An uprooted fir, 50 ins. diam., plainly blazed and healed, the stump hole of which bears N. 70° E., 38 lks. dist.</p> <p style="padding-left: 40px;">A fir snag, 70 ins. diam., bears N. 44$\frac{1}{2}$° W., 88 lks. dist., with blaze opened and decayed.</p> <p>At the corner point</p> <p>Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked</p>