

County Surveyor's Record, Douglas County, Oregon

79

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

From the cor. of secs. 19, 20, 29, and 30.

N. 4° 55' E., bet. secs. 19 and 20.

Ascend 160 ft. over SW. slope, through heavy timber and dense undergrowth.

5.45 Ridge, the divide bet. Bear Creek and Johnson Creek, bears NW. and S. 60° E.; desc. 215 ft. over NE. slope.

15.15 Spur, slopes N. 15° E.; desc. 290 ft. over NW. slope.

22.70 Dry bed of a stream, 4 lks. wide, course N. 30° E.; asc. 70 ft. along E. slope.

27.00 Top of ascent on E. slope; desc. 30 ft. over NE. slope.


28.45 Ravine, course S. 80° E.; asc. 160 ft. over broken SE. slope.

36.50 Spur, slopes N. 20° E.; desc. 160 ft. over NW. slope.

41.00 Spur, slopes N. 15° W.; desc. 70 ft. over NE. slope.

42.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked



from which

A fir, 50 ins. diam., bears S. 37° 45' E., 48 lks. dist., marked $\frac{1}{4}$ S20 BT.

A cedar, 20 ins. diam., bears S. 28 $\frac{1}{4}$ ° W., 29 lks. dist., marked $\frac{1}{4}$ S19 BT.

Descend 300 ft. over N. slope.

43.02 A fir, 40 ins. diam., on line, marked with two hacks each on N. and S. sides.

48.50 Dry bed of stream, 12 lks. wide, course E.; asc. 220 ft. over SE. slope.

53.50 Spur, slopes N. 60° E.; desc. 270 ft. over N. slope.

59.10 Johnson Creek, 15 lks. wide, course S. 70° E.; asc. 530 ft. over S. slope, changing to broken SW. slope.

73.65 High spur, slopes S. 60° W.; desc. 220 ft. over NW. slope.

78.40 Ravine, course N. 80° W.; asc. 100 ft. over broken SW. slope.

82.00 Spur, slopes N. 55° W.; desc. 175 ft. over N. slope.

85.05 Intermittent branch, 3 lks. wide, course N. 75° W.; asc. 40 ft. over SW. slope.