

County Surveyor's Record, Douglas County, Oregon

81

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS 22.00	Top of ascent on N. slope; desc. 270 ft. over broken NW. slope, changing to W. slope.
32.55	Dry bed of stream, 2 lks. wide, course N. 25° W.; desc. 30 ft. along gradual N. slope.
33.50	Branch, 2 lks. wide, course S. 85° W.; asc. 10 ft. along S. slope.
38.10	Top of ascent on S. slope; desc. 5 ft. over SW. slope.
38.50	Intermittent branch, 2 lks. wide, course S. 15° E.; asc. 30 ft. over SE. slope.
39.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \begin{array}{l} S 17 \\ S 20 \end{array}$ 1953 from which A fir, 54 ins. diam., bears N. 51° E., 28 lks. dist., marked $\frac{1}{4}$ S17 BT. A fir, 60 ins. diam., bears S. 76° W., 42 lks. dist., marked $\frac{1}{4}$ S20 BT. Ascend 60 ft. over SE. slope.
41.90	Top of ascent on S. slope; desc. 40 ft. over SW. slope.
43.50	Ravine, course S. 5° W.; asc. 135 ft. over SE. slope.
47.80	Spur, slopes S. 30° W.; desc. 170 ft. over SW. slope.
51.50	Intermittent branch, 3 lks. wide, course S. 10° E.; asc. 330 ft. over E. slope, changing to SE. slope.
61.00	Top of ascent on S. slope; desc. 30 ft. along S. slope.
65.00	Foot of descent on S. slope; asc. 40 ft. over SE. slope.
68.00	Spur ridge, bears NE. and SW.; desc. 220 ft. over steep W. slope.
72.40	Ravine, course SW.; asc. 20 ft. over SE. slope.
73.50	Top of ascent on S. slope; desc. 175 ft. over SW. slope.
78.72	The cor. of secs. 17, 18, 19, and 20. Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, maple, and alder. Undergrowth, vine maple, salmonberry, hazel, evergreen and red huckleberry, rhododendron, arrowwood, and salal.
	N. 89° 25' W., bet. secs. 18 and 19. Descend 115 ft. over SW. slope, through heavy timber and dense undergrowth.
0.34	A fir, 32 ins. diam., on line, marked with two hacks each on E. and W. sides.
4.50	Foot of descent on S. slope; asc. 55 ft. along steep S. slope.