

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS	
9.20	Top of ascent on S. slope; desc. 180 ft. over SW. slope.
14.95	Johnson Creek, 12 lks. wide, in gravel bed 50 lks. wide, course S. 50° E.; asc. 125 ft. over broken NE. slope.
20.60	Dry bed of stream, 2 lks. wide, course NE.; asc. 260 ft. over E. slope, changing to NE. slope.
26.90	Head of ravine, course N. 35° E.; asc. 75 ft. over broken NE. slope.
28.40	Spur, slopes NE.; asc. 10 ft. along broken N. slope.
31.05	Head of ravine, course N. 30° E.; asc. 65 ft. over NE. slope.
32.40	Spur, slopes N. 15° E.; desc. 45 ft. along broken N. slope.
35.60	Ravine, course N.; asc. 160 ft. over NE. slope.
39.05	The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, at record bearing and distance from each of the original bearing trees, as follows: A fir, 48 ins. diam., bears N. 36° E., 17 lks. dist., marked $\frac{1}{4}$ S BT on bark blaze. A fir, 36 ins. diam., bears S. 62 $\frac{1}{2}$ ° W., 37 lks. dist., marked $\frac{1}{4}$ S BT on bark blaze. At the corner point Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked $\frac{1}{4} \begin{array}{l} S 18 \\ S 19 \end{array}$ 1953 The $\frac{1}{4}$ sec. cor. is located in a spur, slopes N. 15° E. <hr/> N. 88° 39' W., beginning new measurement. Descend slightly along N. slope, near top of spur ridge, through heavy timber and dense undergrowth.
2.00	Spur ridge, at E. end of saddle, bears N. 60° W. and S. 60° E.; desc. 115 ft. over SW. slope.
5.40	Head of ravine, course S. 10° W.; asc. 65 ft. over SE. slope.
9.00	Spur, slopes S. 15° W.; desc. 135 ft. over SW. slope.
12.00	Ravine, course S. 5° W., bending to SE. about 1 $\frac{1}{2}$ chs. S. of line; asc. 100 ft. over SE. slope.
15.00	Spur, slopes S. 20° W.; desc. 175 ft. over SW. slope.
18.80	Ravine, course S. 15° W.; desc. 65 ft. along S. slope, changing to SW. slope.
21.55	Intermittent branch, 2 lks. wide, course S. 25° E.; asc. 360 ft. over SE. slope.
29.30	High spur, slopes S.; desc. 60 ft. over SW. slope, changing to broken S. slope.
34.65	Spur, slopes SW.; desc. 175 ft. over steep W. slope.
37.87	The cor. of secs. 13, 18, 19, and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, marked and witnessed as described in the official record.