

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS	
54.35	Ravine, course S. 70° W.; asc. 60 ft. over SW. slope.
55.80	Top of ascent on W. slope; desc. 185 ft. over NW. slope.
59.50	Ravine, course N. 85° W.; along broken W. slope.
61.20	Ravine, course S. 65° W.; asc. 240 ft. over S. slope.
65.50	High spur, slopes N. 80° W.; desc. 265 ft. over NE. slope.
70.30	Ravine, course N. 55° W.; asc. 45 ft. over SW. slope.
72.40	Point of spur, slopes N. 80° W.; desc. 75 ft. over NW. slope.
74.10	Ravine, course S. 65° W.; asc. 200 ft. over S. slope.
77.80	Spur ridge, bears N. 70° E. and S. 80° W.; desc. 150 ft. over N. slope.
80.44	The cor. of secs. 17 and 18, on the S. bdy. of sec. 8, remonumented by Fred Mensch, in 1921, with an iron post, 2 ins. diam., 6 ins. above ground, firmly set, with brass cap marked

T 20 S R 9 W
S 8

S 18 S 17
T 20 S R 9 W
1921

from which

A yew, 18 ins. diam., bears S. 58½° E., 62 lks. dist., marked T20S R9W S17 BT. (A new bearing tree.)

A vine maple, 7 ins. diam., bears S. 50° E., 22 lks. dist., plainly blazed and healed. (A Mensch bearing tree.)

An alder, 40 ins. diam., bears S. 89° W., 40 lks. dist., marked T20S R9W S18 BT on the bark. (A Thiel bearing tree.)

Land, mountainous. Soil, sandy clay loam. Timber, fir, hemlock, cedar, alder, and maple. Undergrowth, vine maple, hazel, arrowwood, salmonberry, evergreen and red huckleberry, rhododendron, thimbleberry, and salal.

From the cor. of secs. 16 and 17, on the S. bdy. of sec. 9.

S. 89° 39' W., along the N. bdy. of sec. 17.

Ascend 65 ft. over steep NE. slope, changing to E. slope, through heavy timber and dense undergrowth.

1.24	The cor. of secs. 8 and 9, on the N. bdy. of sec. 17, monumented by Fred Mensch, in 1921, with an iron post, 2 ins. diam., 8 ins. above ground, firmly set, but rusted through to the concrete core, with brass cap marked
------	--

T 20 S R 9 W
S 8 S 9

S 17
T 20 S R 9 W
1921

At the corner point, in place of the rusted iron post,

Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked