

County Surveyor's Record, Douglas County, Oregon

12529

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 20 S., R. 9 W.

CHAINS

T 20 S | R 9 W
S 8 | S 9
 S 17
 1954

from which the original bearing trees,

A fir, 18 ins. diam., bears N. 60° E., 16 lks. dist.,
plainly blazed and healed.

A fir, 48 ins. diam., bears N. 25° W., 36 lks. dist.,
marked T20S R9W S8 BT on bark blaze.

Deposit the old iron post at base of the new one.

S. 89° 39' W., beginning new measurement.

Ascend 12 ft. over E. slope.

0.46 Ridge, the divide bet. Coon Creek and Johnson Creek, bears N. 30° W.
and S. 30° E.; desc. 160 ft. over SW. slope.

8.10 Ravine, course S.; asc. 45 ft. over SE. slope.

9.90 Spur, slopes S. 20° W.; desc. 440 ft. over broken SW. slope,
changing to W. slope.

22.15 Branch, 5 lks. wide, course S. 30° W.; asc. 130 ft. over SE. slope.

25.90 Top of ascent on S. slope; desc. 35 ft. along broken S. slope.

27.55 Ravine, course S. 20° E.; asc. 280 ft. over E. slope, changing to
SE. slope.

35.50 Top of ascent on S. slope; desc. 30 ft. over SW. slope.

37.76 The $\frac{1}{4}$ sec. cor. of sec. 17 only, remonumented by Fred Mensch, in
1921, with an iron post, 1 in. diam., 9 ins. above ground, firmly
set, but rusted through to the concrete core, with brass cap marked

$\frac{1}{4}$ S 17
1921

At the corner point, in place of the rusted iron post,

Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground,
with brass cap marked

$\frac{1}{4}$ S 17
1954

from which

A fir, 50 ins. diam., bears S. 28° E., 52 lks. dist.,
marked $\frac{1}{4}$ S17 BT. (A new bearing tree.)

A fir snag, 26 ins. diam., bears S. 10° E., 25 lks. dist.,
marked $\frac{1}{4}$ S BT on bark blaze. (A Thiel bearing tree.)

A fir, 50 ins. diam., bears S. 21 $\frac{1}{2}$ ° W., 74 lks. dist.,
plainly blazed and healed. (A Mensch bearing tree;
record, bears S. 20° W., 72 lks. dist.)

Deposit the old iron post at the base of the new one.

N. 89° 28' W., beginning new measurement.