

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy. of T. 26 S., R. 7 W.

CHAINS

Raise a mound of stone, 3½ ft. base, 2 ft. high, west of the cor.
No suitable bearing trees are available.

From this point the cor. of secs. 25, 30, 31, and 36, on the W. bdy. of the Tp., bears S. 0° 01' W., 80.49 chs. dist., perpetuated with a fir post, 4x4 ins., 18 ins. high, firmly set in a mound of stone, 3 ft. base, 1 ft. high, at record bearing and distance from the remains of the original bearing trees:

- The stump hole and roots of a fir, bears N. 64° E., 15 lks. dist.
- A clump of chinquapin sprouts, bears S. 30° E., 37 lks. dist.
- A rotted and burned fir stump, bears S. 22° W., 21 lks. dist.
- The stump hole of a fir, bears N. 44° W., 32 lks. dist.

and locally established bearing trees:

- A fir, 23 ins. diam., bears N. 19° E., 48 lks. dist., with scribe marks 26 visible on a partially healed blaze.
- A fir, 20 ins. diam., bears N. 43° W., 48 lks. dist., with scribe marks BT visible on a partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap marked

T26S	
R8W	R7W
S 25	S 30
S 36	S 31
1959	

from which new bearing trees

- A fir, 18 ins. diam., bears N. 14° E., 40 lks. dist., marked T26S R7W S30 BT.
- A fir, 6 ins. diam., bears S. 16° E., 215 lks. dist., marked T26S R7W S31 BT.
- A fir, 8 ins. diam., bears S. 11° W., 197 lks. dist., marked T26S R8W S36 BT.
- A fir, 26 ins. diam., bears N. 83° W., 20 lks. dist., marked T26S R8W S25 BT.

Reset the fir post alongside the iron post.

N. 0° 01' E. bet. secs. 19 and 24, marking and blazing the true line.

Ascend 138 ft. over SE. slope, through logged and burned area in dense undergrowth.

- 7.65 Spur, slopes E.; descend 366 ft. over NE. slope.
- 19.40 Creek, 3 lks. wide, course E.; ascend 8 ft. over SE. slope.
- 24.65 Spur, slopes E.; dirt road, access, 20 lks. wide, bears E. and W.; descend 66 ft. over gentle N. slope.
- 40.43 The ¼ sec. cor. of secs. 19 and 24, determined at record distance from the remains of the original bearing trees: