

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the W. Bdy., T. 26 S., R. 7 W.

CHAINS

A sawed fir stump, 31 ins. diam., bears N. $3\frac{3}{4}^{\circ}$ E., 58 lks. dist., with illegible scribe marks visible on partly opened blaze. (Record bearing N. 10° E.)

A burned and rotted fir snag, 36 ins. diam., bears N. 29° W., 15 lks. dist., with overgrowth BT and scribe mark B found in the center of the rotted trunk. (Record bearing, N. 38° W.)

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T26S} \\ \text{R8W R7W} \\ \downarrow \\ \text{S 24 | S 19} \\ \downarrow \\ \text{1959} \end{array}$$

from which

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears N. $40\frac{1}{2}^{\circ}$ E., 13 lks. dist., with brass cap marked T26S R7W $\frac{1}{4}$ S19 RM 1959 and an arrow pointing to the corner.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 65° W., 11 lks. dist., with brass cap marked T26S R8W $\frac{1}{4}$ S24 RM 1959 and an arrow pointing to the corner.

No suitable bearing trees are available.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 26 S., R. 7 W.

(Restoring the 1855 survey by Dennis Hathorn and the
1881 survey by A. R. and S. C. Flint.)

From the cor. of secs. 21, 22, 27, and 28, determined at record distance from each of the remaining original bearing trees:

The stump of a burned and rotted madrone with small sprouts, bears S. 16° E., 30 lks. dist.

A rotted and burned fir stump, approx. 20 ins. diam., bears S. 85° W., 26 lks. dist. (Record bearing, S. 82° W.)

A rotted and burned maple stump, 21 ins. diam., with small sprouts, bears N. 20° W., 82 lks. dist.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

$$\begin{array}{c} \text{T26S R7W} \\ \text{S 21 | S 22} \\ \text{S 28 | S 27} \\ \text{1959} \end{array}$$

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

No suitable bearing trees are available.