

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 7 W.

CHAINS	N. 89° 56' W., bet. secs. 21 and 28, marking and blazing the true line.
	Ascend 572 ft. over NE. slope and rock bluff, through logged and burned area.
18.25	Ridge, the divide between Hubbard Creek and Umpqua River drainage, bears NW. and S.; enter dense undergrowth and snag area; desc. 30 ft. over SW. slope.
19.65	Point for E. 1/16 sec. cor. of secs. 21 and 28.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked
	$E \frac{1}{16} \frac{S \ 21}{S \ 28}$
	1959
	from which
	An iron post, 28 ins. long, 2½ ins diam., set 24 ins. in the ground, for a reference monument, bears N. 15° E., 14¾ lks. dist., with brass cap marked E 1/16 S21 RM 1959 and an arrow pointing to the corner.
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 15° W., 14¾ lks. dist., with brass cap marked E 1/16 S28 RM 1959 and an arrow pointing to the corner.
	No suitable bearing trees are available.
	Descend 374 ft. over SW. slope.
22.45	Dirt access road, bears NW. and SE., 20 lks. wide, curving to S.
36.25	Creek, 2 lks. wide, course SW.; descend 3 ft. over SW. slope.
39.30	Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked
	T26S R7W
	$\frac{1}{4} \frac{S \ 21}{S \ 28}$
	1959
	from which
	An iron post, 28 ins. long, 2½ ins diam., set 24 ins. in the ground, for a reference monument, bears North, 11¼ lks. dist., with brass cap marked T26S R7W ¼ S21 RM 1959 and an arrow pointing to the corner.
	An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears South 11¼ lks. dist., with brass cap marked T26S R7W ¼ S28 RM 1959 and an arrow pointing to the corner.
	No suitable bearing trees are available.
	Descend 68 ft. over SW. slope.
45.30	Creek, 4 lks. wide, course NW.; bending to W.; descend 26 ft. over NW. slope.