

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 26 S., R. 7 W.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T26S R7W	
S 17	S 16
S 20	S 21
1959	

from which

A fir, 11 ins. diam., bears S. 16¼° E., 120½ lks. dist., marked T26S R7W S21 BT.

A fir, 14 ins. diam., bears S. 71¾° W., 133 lks. dist., marked T26S R7W S20 BT.

A fir, 10 ins. diam., bears N. 13½° W., 91 lks. dist., marked T26S R7W S17 BT.

Land, mountainous.

Soil, rocky clay and bedrock outcroppings.

Timber, logged and burned; undergrowth, ceanothus, manzanita, poison oak, huckleberry, gooseberry, madrone, and salal.

The cor. of secs. 15, 16, 21 and 22, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, monumented with an iron pipe, 1 in. diam., 6 ins. above ground, firmly set, at record bearing and distance from the only remaining original bearing tree:

A fallen fir, 30 ins. diam., bears S. 5° E., 41 lks. dist.,

and locally established bearing trees:

A white fir, 36 ins. diam., bears N. 18° E., 70 lks. dist., bark scribed S15 CS BT.

A sawed fir stump, 44 ins. diam., bears S. 50° W., 73½ lks. dist., no marks visible.

A white fir, 30 ins. diam., bears N. 57½° W., 36½ lks. dist., bark scribed S16 CS BT.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap marked

T26S R7W	
S 16	S 15
S 21	S 22
1959	

from which new bearing trees

A white fir, 16 ins. diam., bears S. 0° 15' E., 82 lks. dist., marked T26S R7W S22 BT.

A white fir, 16 ins. diam., bears S. 37° W., 51 lks. dist., marked T26S R7W S21 BT.

Deposit the iron pipe alongside the iron post.

The corner falls 1 lk. SW. of a fence corner from which fences extend N. and E.