

Dependent Resurvey of a Portion of the S. Bdy. of T. 21 S., R. 8 W.

CHAINS

from which

SAWED STUMP ONLY ON SEPT. 16, 1963 M.C. H.
 A hemlock, 15 ins. diam., bears N. 57° 45' E., 81 lks. dist.,
 marked $\frac{1}{4}$ S35 BT.

A fir, 15 ins. diam., bears N. 1 $\frac{1}{4}$ ° W., 85 lks. dist.,
 marked $\frac{1}{4}$ S35 BT.

N. 89° 01' W., beginning new measurement.

Descend 31 ft. over NW. slope.

1.75 Paradise Creek, 20 lks. wide, course SW.; asc. 225 ft. over SE. slope.

2.85 Unimproved road, bears NE. and SW.

9.65 Point for the $\frac{1}{4}$ sec. cor. of sec. 2, T. 22 S., R. 8 W. only, at proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, with brass cap marked

$\frac{1}{4}$ S 2
 1952

*FD. OK 3/83
 L. ROBERTS
 M 94-6*

from which

A fir, 48 ins. diam., bears S. 50 $\frac{1}{2}$ ° E., 119 lks. dist.,
 marked $\frac{1}{4}$ S2 BT.

A fir, 70 ins. diam., bears S. 14 $\frac{1}{2}$ ° W., 136 lks. dist.,
 marked $\frac{1}{4}$ S2 BT.

S 14 $\frac{1}{2}$ ° E - M.C. H.

Ascend 5 ft. along S. slope.

12.00 Spur, slopes S.; desc. 64 ft. over W. slope.

16.00 Spring branch, 2 lks. wide, course S. 20° E.; asc. 234 ft. over E. slope.

24.50 Spur, slopes S. 10° W.; desc. 236 ft. along S. slope, changing to SW. slope.

36.50 Spring branch, 1 lk. wide, course SW.; asc. 28 ft. over SE. slope.

37.50 Top of ascent, slopes S.; desc. 10 ft. over W. slope.

38.76 Point for the cor. of secs. 34 and 35 only, determined from the remaining original bearing tree:

A fir, 55 ins. diam., bears N. 30° E., 45 lks. dist.,
 showing old scribe marks in the bark.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, with brass cap marked

T 21 S R 8 W
S 34 | S 35
 S 2
 T 22 S R 8 W
 1952

from which

A fir, 47 ins. diam., bears N. 35 $\frac{1}{2}$ ° E., 92 lks. dist.,
 marked T21S R8W S35 BT.