

## County Surveyor's Record, Douglas County, Oregon

7

## Dependent Resurvey of a Portion of the S. Bdy. of T. 21 S., R. 8 W.

CHAINS

A fir, 35 ins. diam., bears N.  $27\frac{1}{4}^{\circ}$  E., 17 lks. dist.,  
marked  $\frac{1}{4}$  S BT in bark. (Record, N.  $35^{\circ}$  E., 15 lks. dist.)

A fir, 50 ins. diam., bears S.  $11^{\circ} 45'$  W., 41 lks. dist.,  
marked  $\frac{1}{4}$  S BT in bark. (Record, S.  $5^{\circ}$  E., 40 lks. dist.)

N.  $89^{\circ} 24'$  W., beginning new measurement.

Ascend slightly along S. slope.

4.40 High spur and tractor trail, bears NW. and SE.; desc. 217 ft. over SW. slope, through recently burned over timber.

12.02 Point for the  $\frac{1}{4}$  sec. cor. of sec. 3, T. 22 S., R. 8 W., at proportionate distance.

Set an iron post, 3 ft. long, 1 in. diam., 27 ins. in the ground, with brass cap marked

$\frac{1}{4}$  S 3  
1952

FD OK BY ROBERTS  
5/86 CS 63/18  
D. BAKER 5/87 M 101-54

from which

A fir, 45 ins. diam., bears S.  $63^{\circ}$  E., 52 lks. dist.,  
marked  $\frac{1}{4}$  S3 BT.

A fir, 35 ins. diam., bears S.  $7^{\circ} 45'$  W., 124 lks. dist.,  
marked  $\frac{1}{4}$  S3 BT.

Descend 113 ft. over steep SW. slope.

14.25 Ravine, drains SW.; asc. 9 ft. over S. slope.

16.25 Top of ascent, slopes S.; desc. 51 ft. along S. slope.

19.50 Spur, slopes SW.; desc. 74 ft. over SW. slope.

22.15 Spring branch, 2 lks. wide, course SW.; asc. slightly.

23.50 Spur, slopes S.; desc. 93 ft. over SW. slope.

29.05 Creek, 12 lks. wide, course S.  $25^{\circ}$  E.; asc. slightly over NE. slope.

30.17 Branch, 4 lks. wide, course NE.; asc. 276 ft. over very steep E. slope, changing to NE. slope.

38.81 The cor. of secs. 33 and 34, which is marked with an iron post, 2 ins. diam., firmly set, marked and witnessed as described in the official record.

Land, mountainous. Soil, rocky clay. Timber, fir, hemlock, cedar, maple, alder, chinquapin, yew, and madrona. Undergrowth, vine maple, hazel, and poison oak, recently burned over.

Dependent Resurvey of the East Boundary of T. 21 S., R. 8 W.  
(Restoring the 1883 survey by Laban H. Wheeler)

From the cor. of Tps. 21 and 22 S., Rs. 7 and 8 W., hereinbefore described.

N.  $0^{\circ} 15'$  E., bet. secs. 31 and 36, marking and blazing the true line.