


Dependent Resurvey of the East Boundary of T. 21 S., R. 8 W.

CHAINS

- 19.85 Branch, 1 lk. wide, course N. 80° W.; asc. 170 ft. over SW. slope.
- 29.90 Spur, slopes N. 80° W.; desc. 185 ft. over N. slope.
- 33.40 Ravine, course N. 50° W.; asc. 15 ft. over SW. slope.
- 34.65 Spur, slopes NW.; desc. 70 ft. over broken NW. slope.
- 36.50 Branch, 1 lk. wide, course N. 80° W.; asc. 25 ft. over SW. slope.
- 37.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 1 in. diam., 28 ins. in the ground, with brass cap marked




from which

A hemlock, 24 ins. diam., bears S. 73 $\frac{1}{2}$ ° E., 45 lks. dist., marked $\frac{1}{4}$ S18 BT.

A hemlock, 14 ins. diam., bears N. 34° W., 77 lks. dist., marked $\frac{1}{4}$ S13 BT.

Ascend 70 ft. over SW. slope.

- 40.00 Spur, slopes S. 75° W.; asc. 25 ft. along broken W. slope.
- 48.70 Spur, slopes N. 60° W.; desc. 40 ft. over NW. slope.
- 50.30 Ravine, course W.; asc. 30 ft. over SW. slope, changing to W. slope.
- 54.20 Spur, slopes NW.; desc. 130 ft. over NW. slope.
- 56.80 Branch, 1 lk. wide, course N. 80° W.; asc. 130 ft. over SW. slope.
- 66.20 Top of ascent on W. slope; desc. 100 ft. over NW. slope.
- 69.25 Ravine, course N. 60° W.; asc. 40 ft. over SW. slope.
- 72.80 Top of ascent on W. slope; desc. 50 ft. over NW. slope, changing to N. slope.
- 74.80 Point for the cor. of secs. 7, 12, 13, and 18, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap marked



from which

A hemlock, 13 ins. diam., bears N. 48° E., 30 lks. dist., marked T21S R7W S7 BT.

A hemlock, 10 ins. diam., bears S. 58° E., 38 lks. dist., marked T21S R7W S18 BT.